

Specification Sheet

Part Number: 106-60000

Apply 8,000 cable ties with a fully charged Metabo 2.0 Ah battery, for virtually non-stop performance.

Removable handle for space-saving integration into fully automated production lines (Power Pack CPK with control box required).

HT Data Management CPK software included for extensive data evaluation and export function for manufacturing data, further service functions and consistent documentation of every binding process.

Bandoliers of 50 cable ties as well as reels of 5,000 cable ties can be used.

Process-reliable, constant and reproducible bundling and cutting up to 20 mm in diameter.



CPK Hybrid T18RA Automatic Cable Tie Tool, 1/pkg

Article Number	106-60000
Type	Autotool_CPK_hybrid
Color	Dark Blue (DKBU)
Quantity Per	pack

Product Description	The CPK Hybrid (T18RA) is a fully automated cable tying system. It can be powered two ways - electrically with a power pack or with a common CAS lithium-ion battery. It can speed up bundling processes and improve consistency and efficiency. With a single pull of the trigger, the CPK Hybrid delivers a cable tie, wraps it around the bundle, tensions and cuts off the tail. This cable tying system is characterized by its simple operation and user-friendly ergonomics. The CPK Hybrid has preset options and offers an on-tool display for optional setting changes. Increase ergonomics with additional accessories such as the bench mount or overhead suspension options.
Short Description	CPK Hybrid T18RA Automatic Cable Tie Tool, 1/pkg
Global Part Name	Autotool_CPK_hybrid-MET/PL-BU
Minimum Tensile Strength (Imperial)	17.98
Minimum Tensile Strength (Metric)	80
Length L (Imperial)	11.22
Length L (Metric)	285.0
Width W (Imperial)	3.39
Width W (Metric)	86.0
Bundle Diameter Min (Imperial)	0.03
Bundle Diameter Min (Metric)	0.7
Bundle Diameter Max (Imperial)	0.79
Bundle Diameter Max (Metric)	20

Cable Ties	T18RA50, T18RA5000
Cycle Time	0.65-1.0 sec. depending on quality and force
Power supply unit	Electrical
Height H (Imperial)	10.63
Height H (Metric)	270.0
Tension Setting Tools	Adjustable
Power Supply	120VAC or 18V battery
Material	Metal (MET) Plastic (PL)
Material Shortcut	MET PL
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	1
Package Quantity (Metric)	1

Customs Number

8467290095

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)