

## Specification Sheet

Part Number: T120L9K2



Engineered and manufactured for maximum performance and quality.

Made from 100% high-quality plastic to ensure efficient recycling.

Inside serration for a strong grip onto bundles.

Easy application either manually or with a tensioning tool.

Heavy Duty Cable Tie, 30" Long, UL Rated, 120lb Tensile Strength, PA66, Natural, 50/pkg

Article Number 111-12419

Type T120L

Color Natural (NA)

Quantity Per pack

Product Description Heavy duty T-Series cable ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Heavy Duty Cable Tie, 30" Long, UL Rated, 120lb Tensile Strength, PA66, Natural, 50/pkg

|                                     |                 |
|-------------------------------------|-----------------|
| Global Part Name                    | T120L-PA66-NA   |
| Minimum Tensile Strength (Imperial) | 120             |
| Minimum Tensile Strength (Metric)   | 535             |
| Length L (Imperial)                 | 30.0            |
| Length L (Metric)                   | 760.0           |
| Identification Plate Position       | none            |
| Releasable Closure                  | No              |
| Tie Closure                         | plastic pawl    |
| Variant                             | Inside Serrated |
| Width W (Imperial)                  | 0.30            |
| Width W (Metric)                    | 7.6             |
| Bundle Diameter Min (Imperial)      | 0.2             |
| Bundle Diameter Min (Metric)        | 5.0             |
| Bundle Diameter Max (Imperial)      | 8.86            |
| Bundle Diameter Max (Metric)        | 225.0           |
| Thickness T (Imperial)              | 0.075           |

|                                  |                                  |
|----------------------------------|----------------------------------|
| Thickness T (Metric)             | 1.9                              |
| Cable Tie Head Length (Imperial) | 0.39                             |
| Cable Tie Head Width (Imperial)  | 0.51                             |
| Height H (Metric)                | 7.8                              |
| Material                         | Polyamide 6.6 (PA66)             |
| Material Shortcut                | PA66                             |
| Flammability                     | UL 94 V-2                        |
| Halogen Free                     | Yes                              |
| UV Resistant (Yes/No)            | No                               |
| Use Conditions                   | For Indoor Use Only              |
| Plenum Rating                    | AH-2                             |
| Operating Temperature            | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33)     | No                               |
| ROHS Compliant                   | Yes                              |
| Certification/Specification      | UL 62275                         |

UL Recognized (US) Yes

UL Listed (US and Canada) Yes

UL Recognized (US and Canada) Yes

UL Listed (US) Yes

Package Quantity (Imperial) 50

Package Quantity (Metric) 50

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)