

## Specification Sheet

Part Number: TELS-SPOOL



Continuous strap and separate heads allow for any bundle diameter, eliminating waste.

Smooth strap prevents cable damage.

UV resistant materials contain an inhibitor which prolongs the life of the tie in outdoor environments.

Extended-Length Tie, POM, Black, 50' Strap Reel/pkg

Article Number 111-32106

Type TELS-SPOOL

Color Black (BK)

Quantity Per pack

**Product Description** Extended Length Ties provide a high tensile strength strapping system consisting of a continuous strap and separate locking head making it suitable for any bundle diameter, eliminating waste. The smooth strap and specially designed heads with stainless steel pawls provide a strong grip on cables and wires without damage during vibration or in extreme environments. Spacers are available for dual bundle applications.

**Short Description** Extended-Length Tie, POM, Black, 50' Strap Reel/pkg

Global Part Name TELS-SPOOL-POM-BK

Minimum Tensile Strength (Imperial) 250

Minimum Tensile Strength (Metric) 1115

Length L (Imperial) 50.0

Length L (Metric) 15.2

Identification Plate Position none

Releasable Closure No

Tie Closure steel pawl

Variant Endless

Width W (Imperial) 0.5

Width W (Metric) 12.8

Thickness T (Imperial) 0.06

Thickness T (Metric) 1.52

Material Polyacetal (POM)

Material Shortcut POM

Material Cable Tie	Polyacetal (POM)
Material Head	Polyacetal (POM)
Flammability	UL 94 HB
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +194°F (-40°C to +90°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1
Package Quantity (Metric)	1
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)