

Specification Sheet

Part Number: 126-00114



An all-in-one bundling and fixing solution reduces costs.

Disc provides secure insertion and minimizes access of dust, dirt and water.

1-Piece Cable Tie with Arrowhead Mount, 8.5"L, 50lb, Panel Thickness 0.07 - 0.12", PA66HIRHS, Natural, 500/pkg

| | |
|---------------------|--|
| Article Number | 126-00114 |
| Type | T50ROSAH6U |
| Color | Natural (NA) |
| Quantity Per | pack |
| Product Description | The Domed Push Mount Tie provides a tight, rattle-free installation and acts as a seal to keep out dust and debris. One-piece mounting ties offer a complete solution by both bundling cable and at the same time providing a mounting solution. |
| Short Description | 1-Piece Cable Tie with Arrowhead Mount, 8.5"L, 50lb, Panel Thickness 0.07 - 0.12", PA66HIRHS, Natural, 500/pkg |
| Global Part Name | T50ROSAH6U-PA66HIRHS-NA |

| | |
|-------------------------------------|------------------|
| Minimum Tensile Strength (Imperial) | 50 |
| Minimum Tensile Strength (Metric) | 225 |
| Length L (Imperial) | 8.5 |
| Length L (Metric) | 215.9 |
| Fixation Method | Arrowhead |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Outside Serrated |
| Width W (Imperial) | 0.20 |
| Width W (Metric) | 5.0 |
| Bundle Diameter Min (Imperial) | 0.04 |
| Bundle Diameter Min (Metric) | 1.0 |
| Bundle Diameter Max (Imperial) | 1.97 |
| Bundle Diameter Max (Metric) | 50.0 |
| Panel Thickness Min (Imperial) | 0.07 |

| | |
|---|--|
| Panel Thickness Max (Imperial) | 0.12 |
| Panel Thickness Min (Metric) | 1.8 |
| Panel Thickness Max (Metric) | 3.0 |
| Mounting Hole Diameter D (Imperial) | 0.24 - 0.27 |
| Mounting Hole Diameter D (Metric) | 6.1 - 6.9 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.24 |
| Mounting Hole Diameter D Max (Imperial) | 0.27 |
| Mounting Hole Diameter D Max (Metric) | 6.9 |
| Disc Diameter (Metric) | 16.0 |
| Disc Diameter (Imperial) | 0.63 |
| Material | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Material Shortcut | PA66HIRHS |
| Flammability | UL 94 HB |
| UV Resistant (Yes/No) | No |
| Use Conditions | For Indoor Use Only |

Operating Temperature -40°F to +230°F (-40°C to +110°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)