

Specification Sheet

Part Number: 132-00050



Intuitive one-piece design eliminates the need for multiple components, simplifying assembly.

Integrated pilot bushing ensures secure fit in hole and provides abrasion protection.

High impact modified, heat-resistant, UV stabilized material is ideal for long-term performance, even in extreme weather.

Button Head Cable Tie, 15.4" L, 4.13" Max Bundle Dia, 0.25" Panel, 150 lb, PA66HIRHSUV, Black, 2000/ctn

Article Number	132-00050
----------------	-----------

Type	BT150L1PC
------	-----------

Color	Black (BK)
-------	------------

Quantity Per	pack
--------------	------

Product Description	This 1-piece button head mount secures cables and wire bundles to panels. The design allows the strap to be wrapped clockwise or counter-clockwise around the bundle, assisting the installer by removing the necessity to first check the tie's orientation. Made from impact-modified, heat-resistant, UV stabilized Polyamide 6.6 material, it will withstand extreme environments.
---------------------	--

Short Description	Button Head Cable Tie, 15.4" L, 4.13" Max Bundle Dia, 0.25" Panel, 150 lb, PA66HIRHSUV, Black, 2000/ctn
-------------------	---

Global Part Name	BT150L1PC-PA66HIRHSUV-BK
------------------	--------------------------

Minimum Tensile Strength (Imperial)	150
-------------------------------------	-----

Minimum Tensile Strength (Metric)	667
-----------------------------------	-----

Length L (Imperial)	15.4
---------------------	------

Length L (Metric)	390.9
-------------------	-------

Fixation Method	Button Head
-----------------	-------------

Identification Plate Position	none
-------------------------------	------

Releasable Closure	No
--------------------	----

Tie Closure	plastic pawl
-------------	--------------

Variant	Inside/Outside Serrated
---------	-------------------------

Width W (Imperial)	0.29
--------------------	------

Width W (Metric)	7.4
------------------	-----

Bundle Diameter Min (Imperial)	0.24
--------------------------------	------

Bundle Diameter Min (Metric)	6.0
------------------------------	-----

Bundle Diameter Max (Imperial)	4.13
--------------------------------	------

Bundle Diameter Max (Metric)	105.0
------------------------------	-------

Thickness T (Imperial)	0.06
Thickness T (Metric)	1.6
Height H (Imperial)	0.29
Height H (Metric)	7.4
Panel Thickness Min (Imperial)	0.25
Panel Thickness Min (Metric)	6.35
Mounting Hole Diameter D (Imperial)	0.43 - 0.79 "
Mounting Hole Diameter D (Metric)	11.0 - 20.0 mm
Mounting Hole Diameter D Min (Imperial)	0.43
Mounting Hole Diameter D Max (Imperial)	0.79
Mounting Hole Diameter D Max (Metric)	20.0
Disc Diameter (Metric)	25.8
Disc Diameter (Imperial)	1.02
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV

Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	2000
Package Quantity (Metric)	2000
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224
 Phone: (800) 537-1512 | Email: corp@htamericas.com