

Specification Sheet

Part Number: 133-03474

Clamp includes an internal rib that spans the inside of the bracket to fit securely into the profile of the tubing to prevent lateral movement and slipping of the tubing.

Fir tree design provides low insertion force and high extraction force.

Extended fir tree allows for a wide range of panel thicknesses.



Convolute Tubing Clamp, Size 25, 6.5 mm Hole Dia., 40.5 mm Offset, PA66, Black, 500/carton

Article Number 133-03474

Type CDC25S40M6

Color Black (BK)

Quantity Per carton

Product Description Convolute Tubing Clamps provide a quick and easy method for firmly securing corrugated tubing to a surface. This application is popular in a variety of industries such as the wire harness, automotive, trucking and heavy equipment manufacturing industries.

Short Description Convolute Tubing Clamp, Size 25, 6.5 mm Hole Dia., 40.5 mm Offset, PA66, Black, 500/carton

Global Part Name CDC25S40M6-PA66HS-BK

Length L (Imperial)	2.94
Length L (Metric)	74.8
Offset Length (Imperial)	1.59
Offset Length (Metric)	40.5
Fixation Method	screwable
Width W (Imperial)	0.9
Width W (Metric)	23.0
Bundle Diameter Max (Imperial)	0.98
Bundle Diameter Max (Metric)	25.0
Height H (Imperial)	3.13
Height H (Metric)	79.6
Diameter D (Imperial)	1.06
Diameter D (Metric)	27.0
Mounting Hole Diameter D (Imperial)	0.25 - 0.26 "
Mounting Hole Diameter D (Metric)	6.4 - 6.6 mm
Mounting Hole Diameter D Min (Imperial)	0.25

Mounting Hole Diameter D Max (Imperial) 0.26

Mounting Hole Diameter D Max (Metric) 6.6

Stud Diameter (Metric) M6

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL 94 V-2

Halogen Free No

UV Resistant (Yes/No) No

Use Conditions For Indoor and Outdoor Use

Operating Temperature -40°F to +185°F (-40°C to +85°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)