

## Specification Sheet

Part Number: 151-01296

HellermannTyton connector clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications.

Detailed designs include anti-rattle disc features, anti-rotation oval fir trees, and clamps for mounting on edges.



HellermannTyton offers an assortment of connector clips that are available for a variety of connector slot designs found on most of the largest global connector manufacturers.

Connector Clip with Oval Fir Tree, 9.0 - 17.0mm Hole Dia, PA66HIRHSUV, Black, 3000/carton

Article Number 151-01296

Type CC18

Color Black (BK)

Quantity Per pack

**Product Description** Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

|                                     |   |
|-------------------------------------|---|
| Short Description                   | Connector Clip with Oval Fir Tree, 9.0 - 17.0mm Hole Dia, PA66HIRHSUV, Black, 3000/carton |
| Global Part Name                    | CC18-PA66HIRHSUV-BK   |
| Minimum Tensile Strength (Imperial) | 35  |
| Minimum Tensile Strength (Metric)   | 155   |
| Length L (Imperial)                 | 1.19  |
| Length L (Metric)                   | 30.29   |
| Fixation Method                     | Fir Tree for oval holes   |
| Width W (Imperial)                  | 0.80  |
| Width W (Metric)                    | 20.32   |
| Height H (Imperial)                 | 0.93  |
| Height H (Metric)                   | 23.57   |
| Panel Thickness Min (Imperial)      | 0.02  |
| Panel Thickness Max (Imperial)      | 0.37  |
| Panel Thickness Min (Metric)        | 0.6   |
| Panel Thickness Max (Metric)        | 9.5   |
| Mounting Hole Diameter D (Imperial) | 0.35 x 0.67 "   |

Mounting Hole Diameter D (Metric) 9.0 x 17.0 mm

Mounting Hole Diameter D Min (Imperial) 0.35

Mounting Hole Diameter D Max (Imperial) 0.35

Mounting Hole Diameter D Max (Metric) 9.0

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

UV Resistant (Yes/No) Yes

Use Conditions For Indoor and Outdoor Use

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

Package Quantity (Imperial) 3000

Package Quantity (Metric) 3000

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)