

Specification Sheet

Part Number: 151-01869

Connector Clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications.

HellermannTyton offers connector clips with robust and detailed designs that include anti-rattle disc features, anti-rotation oval fir trees, and clamps for mounting on edges.



HellermannTyton offers an assortment of connector clips that are available for a variety of connector slot designs found on most of the largest global connector manufacturers.

Connector Clip, Hole Dia. 6.5(+/- 0.2)mm, Panel 0.7-1.3mm, PA66HIRHS, Black, 500/Pack

Article Number 151-01869

Type YCKSFT6.5

Color Black (BK)

Quantity Per bag

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

| | |
|---|---|
| Short Description | Connector Clip, Hole Dia. 6.5(+/- 0.2)mm, Panel 0.7-1.3mm, PA66HIRHS, Black, 500/Pack |
| Global Part Name | YCCKSFT6.5-PA66HIRHS-BK |
| Length L (Imperial) | 1.06 |
| Length L (Metric) | 27.0 |
| Fixation Method | Arrowhead (Small Mount) |
| Width W (Metric) | 16.0 |
| Height H (Imperial) | 0.43 |
| Height H (Metric) | 10.9 |
| Panel Thickness Min (Imperial) | 0.03 |
| Panel Thickness Max (Imperial) | 0.05 |
| Panel Thickness Min (Metric) | 0.7 |
| Panel Thickness Max (Metric) | 1.3 |
| Mounting Hole Diameter D (Imperial) | 0.25 - 0.26 |
| Mounting Hole Diameter D (Metric) | 6.3 - 6.7 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.25 |
| Mounting Hole Diameter D Max (Imperial) | 0.26 |

Mounting Hole Diameter D Max (Metric) 6.7

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL 94 HB

Use Conditions For Indoor and Outdoor Use

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)