

Specification Sheet

Part Number: 151-03389

Clip includes an internal rib that spans the inside of the bracket to fit securely into the profile of the tubing to prevent lateral movement.

Standard LOC design allows for easy installation and serviceability of the bundle.

360-degree enclosure ensures the entire bundle is secure.

Disc around fir tree mitigates potential rattling from vibration.

Versatile, high-performance fir tree design demonstrates easy installation with high pull-out resistance in the four most common hole sizes.



LOC Locking Clamp, 15-19 mm, with 4 x Oval Fir Tree, PA66HIRHSUV, Black, 1000/ctn

Article Number 151-03389

Type LOC15-19RFTOVALR

Color Black (BK)

Quantity Per carton

Product Description This LOC clamp is made specifically for convoluted tubing with 15-19 mm bundle sizes. A convoluted ring feature locks tubing in place.

Short Description LOC Locking Clamp, 15-19 mm, with 4 x Oval Fir Tree, PA66HIRHSUV, Black, 1000/ctn

Global Part Name

LOC15-19RFTOVALR-PA66HIRHSUV-BK

Length L (Imperial) 1.67

Length L (Metric) 42.4

Fixation Method Fir Tree

Width W (Imperial) 1.67

Width W (Metric) 12.0

Bundle Diameter Min (Imperial) 0.59

Bundle Diameter Min (Metric) 15.0

Bundle Diameter Max (Imperial) 0.75

Bundle Diameter Max (Metric) 19.0

Height H (Imperial) 2.5

Height H (Metric) 63.94

Depth D (Imperial) 0.93

Panel Thickness Min (Imperial) 0.02

Panel Thickness Max (Imperial) 0.26

Panel Thickness Min (Metric) 0.6

Panel Thickness Max (Metric)	6.75
Mounting Hole Diameter D (Imperial)	0.24 x 0.48 " 0.26 x 0.49 " 0.28 x 0.47 " 0.26 x 0.51 "
Mounting Hole Diameter D (Metric)	6.2 - 12.2 mm 6.5 x 12.5 mm 7.0 x 12.0 mm 6.5 x 13.0 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.51
Mounting Hole Diameter D Max (Metric)	13.0
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes

Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)