

Specification Sheet

Part Number: 151-03473

Bundling clip allows bundle to be parallel, perpendicular or offset from the panel and mounting hole for routing versatility.

Compact I-beam design provides a robust solution for all bundles, small to large.

Used in conjunction with HellermannTyton's 4x oval push pins, bundling clip prevents rotation of the bundle.

Oval hole can also be used as a portable hole joining two routings together.



Bundling Clip with Round Fir Tree, 2.20" L, 0.02 - 0.23" Panel Thickness, PA66HIRHSUV, Black, 2500/ctn

Article Number	151-03473
Type	BC56FT6.5
Color	Black (BK)
Quantity Per	pack
Product Description	HellermannTyton's bundling clips allow a harness to be routed around a corner and attached to the panel at this location.
Short Description	Bundling Clip with Round Fir Tree, 2.20" L, 0.02 - 0.23" Panel Thickness, PA66HIRHSUV, Black, 2500/ctn
Global Part Name	BC56FT6.5-PA66HIRHSUV-BK

Length L (Imperial)	2.20
Length L (Metric)	56.0
Fixation Method	Fir tree for round holes
Width W (Imperial)	0.31
Width W (Metric)	8.0
Height H (Imperial)	0.77
Height H (Metric)	19.7
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.23
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.24 - 0.28 "
Mounting Hole Diameter D (Metric)	6.1 - 7.0 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.28
Mounting Hole Diameter D Max (Metric)	7.0

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	2500
Package Quantity (Metric)	2500
Customs Number	3926909988

