

## Specification Sheet

Part Number: 151-03512

Connector clip design complies to USCAR EWCAP-005-7 clip slot design and testing specifications.

Mount design provides low insertion with high extraction resistance for easy installation and reliable performance.



Features a fir tree designed for 8mm holes and is made with PA46 material for high heat applications.

Connector Clip with Fir Tree, 7mm, 0.60-6.0 mm Panel Thickness, PA46, Black, 3000/ctn

Article Number	151-03512
Type	CC7FT8LG
Color	Black (BK)
Quantity Per	carton
Product Description	7 mm connector clips made with new ergonomically friendly fir tree and connector clip design that complies with USCAR design and performance standards.
Short Description	Connector Clip with Fir Tree, 7mm, 0.60-6.0 mm Panel Thickness, PA46, Black, 3000/ctn
Global Part Name	CC7FT8LG-PA46-BK

Length L (Imperial)	0.95
Length L (Metric)	24.2
Fixation Method	Fir Tree
Width W (Imperial)	0.29
Width W (Metric)	7.45
Height H (Imperial)	0.81
Height H (Metric)	20.7
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.24
Panel Thickness Min (Metric)	0.60
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.30 - 0.33
Mounting Hole Diameter D (Metric)	7.6 - 8.4 mm
Mounting Hole Diameter D Min (Imperial)	0.30
Mounting Hole Diameter D Max (Imperial)	0.33
Mounting Hole Diameter D Max (Metric)	8.4

Material	Polyamide 4.6 (PA46)
Material Shortcut	PA46
Flammability	UL 94 HB
Halogen Free	Yes
Use Conditions	For Indoor Use Only
Operating Temperature	-40°F to +266°F (-40°C to +130°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	3000
Package Quantity (Metric)	3000
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224  
Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)