## **HellermannTyton**

## **Specification Sheet**

Part Number: 151-03653



No drilling or extra hardware required – just position on steel surface.

Magnetic mounts are reliable even in debris, dirt and oil.

Use for permanent mounting or as a temporary installation tool.

Reuse and reposition capabilities allow for a flexible mounting solution.

Easily remove without leaving residue behind.

Magnetic J-Hook 3/4" Dia Hook, Side Mount, Neodymium Magnet/Steel, 90lb Pull Force, 10/box

Article Number 151-03653 MAGJH90SXS Type Color Metal (ML) **Quantity Per** pack Product Description Magnetic J-hooks route cables by securing to steel surfaces without the need for a mounting hole. Simply hang cables within the J-hook and position the magnet onto the beam, metal joist, ceiling channel, conveyor frame, or other steel surface. Magnetic J-hooks are ideal for supporting communication and data cables. The mounts are simple to secure and can attach to surfaces contaminated with oil or debris. Ultra-strong neodymium magnets are ideal as a permanent mount or for temporary applications. Reuse and reposition them for ultimate flexibility without needing to replace or repurchase parts.

Short Description	Magnetic J-Hook 3/4" Dia Hook, Side Mount, Neodymium Magnet/Steel, 90lb Pull Force, 10/box
Global Part Name	MAGJH90SXS-NDFEB45M/ST-ML
Fixation Method	Magnet
Width W (Imperial)	0.88
Width W (Metric)	22.3
Height H (Imperial)	2.74
Height H (Metric)	69.6
Depth D (Imperial)	0.85
Depth D (Metric)	21.6
Diameter D (Imperial)	1.57
Diameter D (Metric)	40.0
Material	Neodymium alloy 45M (NDFEB45M) Steel (ST)
Material Shortcut	ST NDFEB45M
Halogen Free	Yes

UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Operating Temperature	-40°F to +176°F (-40°C to +80°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	10
Package Quantity (Metric)	10
Customs Number	8505110070

## 7930 N. Faulkner Road, Milwaukee, WI 53224 Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved. Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions