

## Specification Sheet

Part Number: 151-03908

Integrated design allows for easy insertion by hand.

1.0 - 3.0 mm panel thickness range allows for multiple applications.

Double-compression design can accommodate up to 2 wires or cables of varying sizes.

Presents a high extraction force for withstanding extreme conditions.



Heavy Duty Metal Edge Clip, 1 - 3mm Panel Thickness, 5 - 7.6mm Cable Range, SS304, 5000/box

|                |           |
|----------------|-----------|
| Article Number | 151-03908 |
|----------------|-----------|

|      |      |
|------|------|
| Type | MSC2 |
|------|------|

|       |            |
|-------|------------|
| Color | Metal (ML) |
|-------|------------|

|              |      |
|--------------|------|
| Quantity Per | pack |
|--------------|------|

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | HellermannTyton's Heavy Duty Metal Edge Clip provides an excellent alternative to managing up to 2 wire and PV cables where plastic fasteners are not the preferred method. Designed for effortless insertion, the Heavy Duty Edge Clip has a high extraction force that tolerates extreme environments and provides assurance that the cables are secure on a panel. This Metal Edge Clip is simple to install and can easily be removed with a flathead screwdriver. |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                |                                                                                             |
|--------------------------------|---------------------------------------------------------------------------------------------|
| Short Description              | Heavy Duty Metal Edge Clip, 1 - 3mm Panel Thickness, 5 - 7.6mm Cable Range, SS304, 5000/box |
| Global Part Name               | MSC2-SS304-ML                                                                               |
| Length L (Imperial)            | 0.95                                                                                        |
| Length L (Metric)              | 24.1                                                                                        |
| Width W (Imperial)             | 0.50                                                                                        |
| Width W (Metric)               | 13.0                                                                                        |
| Panel Thickness Min (Imperial) | 0.04                                                                                        |
| Panel Thickness Max (Imperial) | 0.12                                                                                        |
| Panel Thickness Min (Metric)   | 1.0                                                                                         |
| Panel Thickness Max (Metric)   | 3.0                                                                                         |
| Material                       | Stainless Steel (SS304)                                                                     |
| Material Shortcut              | SS304                                                                                       |
| Halogen Free                   | Yes                                                                                         |
| UV Resistant (Yes/No)          | Yes                                                                                         |

|                               |                                     |
|-------------------------------|-------------------------------------|
| Use Conditions                | For Indoor and Outdoor Use          |
| Operating Temperature         | -112°F to +1000°F (-80°C to +538°C) |
| Reach Compliant (Article 33)  | Yes                                 |
| ROHS Compliant                | Yes                                 |
| UL Recognized (US)            | Yes                                 |
| UL Listed (US and Canada)     | Yes                                 |
| UL Recognized (US and Canada) | Yes                                 |
| UL Listed (US)                | Yes                                 |
| Package Quantity (Imperial)   | 5000                                |
| Package Quantity (Metric)     | 5000                                |
| Customs Number                | 7326908695                          |

7930 N. Faulkner Road, Milwaukee, WI 53224  
 Phone: (800) 537-1512 | Email: corp@htamericas.com