

Specification Sheet

Part Number: 151-03968

Two clamps with 360-degree enclosures ensure both bundles are secure when being routed.

Clamp can be opened for bundle maintenance.

Versatile high-performance fir tree design demonstrates easy installation with high pull-out resistance in the four most common hole sizes.



Dual LOC Locking Clamp, 18-22 mm, with 4 x Oval Fir Tree, PA66HIRHSUV, Black, 600/ctn

Article Number 151-03968

Type DBLEClamp18-22FTOVAL

Color Black (BK)

Quantity Per carton

Product Description Designed for coupling and mounting double routings, this clamp features HellermannTyton's LOC with an oval fir tree. The versatile high performance fir tree design demonstrates easy installation with high pull-out resistance in the four most common hole sizes. Anti-rotational oval fastener forces bundle to travel in intended direction.

Short Description Dual LOC Locking Clamp, 18-22 mm, with 4 x Oval Fir Tree, PA66HIRHSUV, Black, 600/ctn

Global Part Name DBLEClamp18-22FTOVAL-PA66HIRHSUV-BK

Length L (Imperial) 2.58

Length L (Metric) 65.5

Fixation Method Fir Tree

Bundle Diameter Min (Imperial) 0.71

Bundle Diameter Min (Metric) 18.0

Bundle Diameter Max (Imperial) 0.87

Bundle Diameter Max (Metric) 22.0

Height H (Imperial) 1.68

Height H (Metric) 42.6

Depth D (Imperial) 0.79

Depth D (Metric) 20.0

Panel Thickness Min (Imperial) 0.02

Panel Thickness Max (Imperial) 0.27

Panel Thickness Min (Metric) 0.60

Panel Thickness Max (Metric) 6.75

Mounting Hole Diameter D (Imperial)	0.24 x 0.48 " ; 0.26 x 0.49 " ; 0.26 x 0.51 " ; 0.28 x 0.47 "
Mounting Hole Diameter D (Metric)	6.2 x 12.2 mm 6.5 x 12.5 mm 7.0 x 12.0 mm 6.5 x 13.0 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.51
Mounting Hole Diameter D Max (Metric)	13.0

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL 94 HB

Halogen Free Yes

UV Resistant (Yes/No) Yes

Use Conditions For Indoor and Outdoor Use

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 600

Package Quantity (Metric) 600

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)