

## Specification Sheet

Part Number: 151-04035



No drilling or extra hardware required – just secure to steel surface.

Magnetic mounts are reliable even in debris, dirt, and oil.

Use for permanent mounting or as a temporary installation tool.

Reuse and reposition capabilities allow for a flexible mounting solution.

Easily remove without residue.

Magnetic Bridle Ring, Medium, 1 ¼" Dia Ring, Neodymium Magnet/Steel, 90lb Pull Force, 10/Box

Article Number 151-04035

Type MAGBR90M

Color Metal (ML)

Quantity Per pack

**Product Description**

Magnetic bridle rings route cables by securing to steel surfaces without the need for a mounting hole. Simply attach cables within the bridle ring and position the magnet onto the beam, metal joist, ceiling channel, conveyor frame, or other steel surface. Magnetic bridle rings are ideal for supporting communication and data cables. The mounts are simple to secure and can attach to surfaces contaminated with oil or debris. Ultra-strong neodymium magnets are ideal as a permanent mount or for temporary applications. Reuse and reposition them for ultimate flexibility without needing to replace or repurchase parts.

Short Description	Magnetic Bridle Ring, Medium, 1 ¼" Dia Ring, Neodymium Magnet/Steel, 90lb Pull Force, 10/Box
Global Part Name	MAGBR90M-NDFEB45M/ST-ML
Fixation Method	Magnet
Height H (Imperial)	3.2
Height H (Metric)	81.12
Diameter D (Imperial)	1.57
Diameter D (Metric)	40
Material	Neodymium alloy 45M (NDFEB45M) Steel (ST)
Material Shortcut	ST NDFEB45M
Halogen Free	Yes
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Plenum Rating	AH-2
Operating Temperature	-40°F to +176°F (-40°C to +80°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 10

Package Quantity (Metric) 10

Customs Number 8505110070

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)