

## Specification Sheet

Part Number: 151-04043



No drilling or extra hardware required – just position on steel surface.

Magnetic mounts are reliable even in debris, dirt and oil.

Use for permanent mounting or as a temporary installation tool.

Reuse and reposition capabilities allow for a flexible mounting solution.

Easily remove without leaving residue behind.

Magnetic J-Hook 1 5/16" dia hook, side mount, Neodymium Magnet/Steel, 90lb pull force, 25/box

|                |           |
|----------------|-----------|
| Article Number | 151-04043 |
|----------------|-----------|

|      |           |
|------|-----------|
| Type | MAGJH90SS |
|------|-----------|

|       |                        |
|-------|------------------------|
| Color | Zinc-plated Metal (BV) |
|-------|------------------------|

|              |      |
|--------------|------|
| Quantity Per | pack |
|--------------|------|

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | <p>Magnetic J-hooks route cables by securing to steel surfaces without the need for a mounting hole. Simply hang cables within the J-hook and position the magnet onto the beam, metal joist, ceiling channel, conveyor frame, or other steel surface. Magnetic J-hooks are ideal for supporting communication and data cables. The mounts are simple to secure and can attach to surfaces contaminated with oil or debris. Ultra-strong neodymium magnets are ideal as a permanent mount or for temporary applications. Reuse and reposition them for ultimate flexibility without needing to replace or repurchase parts.</p> |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                       |                                                                                               |
|-----------------------|-----------------------------------------------------------------------------------------------|
| Short Description     | Magnetic J-Hook 1 5/16" dia hook, side mount, Neodymium Magnet/Steel, 90lb pull force, 25/box |
| Global Part Name      | MAGJH90SS-NDFEB45M/ST-ML                                                                      |
| Fixation Method       | Magnet                                                                                        |
| Width W (Imperial)    | 1.32                                                                                          |
| Width W (Metric)      | 33.53                                                                                         |
| Height H (Imperial)   | 3.88                                                                                          |
| Height H (Metric)     | 98.43                                                                                         |
| Depth D (Imperial)    | 1.55                                                                                          |
| Depth D (Metric)      | 39.37                                                                                         |
| Material              | Neodymium alloy 45M (NDFEB45M) Steel (ST)                                                     |
| Material Shortcut     | ST NDFEB45M                                                                                   |
| Halogen Free          | Yes                                                                                           |
| UV Resistant (Yes/No) | No                                                                                            |
| Use Conditions        | For Indoor Use Only                                                                           |

|                              |                                  |
|------------------------------|----------------------------------|
| Plenum Rating                | AH-2                             |
| Operating Temperature        | -40°F to +176°F (-40°C to +80°C) |
| Reach Compliant (Article 33) | Yes                              |
| ROHS Compliant               | Yes                              |
| Package Quantity (Imperial)  | 25                               |
| Package Quantity (Metric)    | 25                               |
| Customs Number               | 8505110070                       |

7930 N. Faulkner Road, Milwaukee, WI 53224  
Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.  
[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)