

Specification Sheet

Part Number: 151-04156

Accommodates T18 - T120 cable ties to suit a variety of applications.

Built-in CutZone safety feature prevents damage to wires and cables when cutting off cable ties for rework.

Unique EZ Feed cable tie slot eliminates common obstructions for faster completion.



Anchor using a #8 (M4) screw or T-nut in frame for flexibility of frame size and mounting location.

Cable Tie Saddle Mount, 1.1 x 0.66", 0.2" Hole Dia, 0.33" Max Tie Width, PA66HS, Black, 100/bag

Article Number 151-04156

Type CTSM3CZS

Color Black (BK)

Quantity Per pack

Product Description This multi-feature saddle mount can route separate wire runs, air hoses or heavy cable bundles. It can be secured with a screw or T-nut. The high points of the mount feature wire troughs that help stabilize and guide cables. Mount accepts a variety of heavy duty cable ties up to 8.3 mm wide. Ideal for many industries from agriculture to truck manufacturing.

Short Description	Cable Tie Saddle Mount, 1.1 x 0.66", 0.2" Hole Dia, 0.33" Max Tie Width, PA66HS, Black, 100/bag
Global Part Name	CTSM3CZS-PA66HS-BK
Length L (Imperial)	1.1
Length L (Metric)	28.0
Fixation Method	Screw Mounting and Rivet
Width W (Imperial)	0.66
Width W (Metric)	16.8
Height H (Imperial)	0.46
Height H (Metric)	11.7
Cable Tie Width Max (Imperial)	0.33
Cable Tie Width Max (Metric)	8.4
Mounting Hole Diameter D (Imperial)	0.21 "
Mounting Hole Diameter D (Metric)	5.35 mm
Material	Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut	PA66HS
Flammability	UL 94 V-2
Halogen Free	Yes
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)