

## Specification Sheet

Part Number: 151-04186



The 360-degree enclosure ensures the entire bundle is secure.

Locking tab is small enough that it will not interfere with any other portion of the wire routing, but is significant enough to allow for manual disengagement if service is needed.

Disc around the fir tree eliminates potential debris and water to enter the panel hole.

LOC Locking Clamp, 25-30 mm, 6.5 mm Fir Tree, PA46, Gray, 1000/ctn

Article Number	151-04186
Type	LOC25-30FT6.5
Color	Gray (GY)
Quantity Per	carton
Product Description	HellermannTyton's Locking Clamp is ideal for fastening wire and cable bundles to panels. The special design dynamically fits various bundle sizes. Its uniquely engineered fir tree holds tightly in pre-stamped 6.5 mm holes. It is easy to install and operate with a single hand and does not require tools, saving time and labor costs.
Short Description	LOC Locking Clamp, 25-30 mm, 6.5 mm Fir Tree, PA46, Gray, 1000/ctn

Global Part Name LOC25-30FT6.5-PA46-GY

Length L (Imperial) 2.5

Length L (Metric) 63.5

Fixation Method Fir Tree

Width W (Imperial) 0.59

Width W (Metric) 15.0

Bundle Diameter Min (Imperial) 0.98

Bundle Diameter Min (Metric) 25.0

Bundle Diameter Max (Imperial) 1.18

Bundle Diameter Max (Metric) 30.0

Height H (Imperial) 2.1

Height H (Metric) 53.2

Depth D (Imperial) 0.59

Depth D (Metric) 15.0

Panel Thickness Min (Imperial) 0.02

Panel Thickness Max (Imperial) 0.16

Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	4.0
Mounting Hole Diameter D (Imperial)	0.24 - 0.26 (hexagonal) "0.24 - 0.28 "
Mounting Hole Diameter D (Metric)	6.1 - 7.0 mm 6.1 - 6.6 mm (hexagonal)
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.28
Mounting Hole Diameter D Max (Metric)	7.0

Material Polyamide 4.6 (PA46)

Material Shortcut PA46

Flammability UL 94 HB

Halogen Free Yes

Use Conditions For Indoor Use Only

Operating Temperature -40°F to +266°F (-40°C to +130°C)

ROHS Compliant Yes

Package Quantity (Imperial) 1000

Package Quantity (Metric) 1000

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)