

Specification Sheet

Part Number: 151-04385



- Compact size for mounting in tight spaces.
- Fine-pitch ratchet provides controlled grip for a range of bundle sizes with one part.
- Fully enclosed clamp prevents crushing and fallout.
- Release latch with simple twist of screwdriver.
- Nexttracker-specific stainless steel mounting hanger designed for severe weather and single-axis tracker movement.

Ratchet O-Clamp, M8 Solar Attachment, 0.73 - 0.88 Bundle Dia, PA66HIRHSUV, BK, 200/ctn

Article Number	151-04385
Type	ROC18.5-22.5NXT
Color	Black (BK)
Quantity Per	carton
Product Description	The Ratchet O-Clamp for Nexttracker attaches easily to Nexttracker torque tubes. It offers one-handed, toolless simplicity and size versatility for managing wires and cables on solar modules. The robust design and solar-optimized materials make it ideal for heavy duty, outdoor applications. The one-piece adjustable clamp can be closed by hand to the desired diameter, replacing multiple sizes for single-diameter fasteners.

Short Description	Ratchet O-Clamp, M8 Solar Attachment, 0.73 - 0.88 Bundle Dia, PA66HIRHSUV, BK, 200/ctn
Global Part Name	ROC18.5-22.5NXT -PA66HIRHSUV/SS-BK
Minimum Tensile Strength (Imperial)	100
Minimum Tensile Strength (Metric)	445
Length L (Imperial)	2.29
Length L (Metric)	58.1
Fixation Method	Mounting Hanger
Width W (Imperial)	1.14
Width W (Metric)	28.9
Bundle Diameter Min (Imperial)	0.73
Bundle Diameter Min (Metric)	18.5
Bundle Diameter Max (Imperial)	0.88
Bundle Diameter Max (Metric)	22.5
Height H (Imperial)	3.30
Height H (Metric)	83.7

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Stainless Steel (SS)
Material Shortcut	PA66HIRHSUV SS
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	200
Package Quantity (Metric)	200
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224
 Phone: (800) 537-1512 | Email: corp@htamericas.com