

Specification Sheet

Part Number: 151-04553

Adds separation in ½" increments, providing flexible spacing options as fiber cable approaches and enters aerial splice enclosure.

Textured surfaces and V-shape corners make it easier to handle and assemble, even when wearing gloves.

Cradle pocket styling creates nesting point for additional spacers, simplifying installation and assembly.

Open front design creates visual orientation to assist with assembly while feeding Aerial Support Tie's bent tail back through loop location for quicker installation.

Snap-fit assembly makes it easy to adjust spacing as needed.

UV material is well suited for extended outdoor applications.



Aerial Support Tie Spacer, PA66HIRHSUV, Black, 50/pkg

Article Number 151-04553

Type TASPGR1

Color Black (BK)

Quantity Per bag

Product Description	The stackable Aerial Support Tie Spacer snaps onto the top of the single-piece Aerial Support Tie and into additional spacer units. The stacking of spacers increases separation between the parallel messenger cable and fiber optic cables for aerial splice enclosure applications. Maintaining separation is important to avoid damage and create more streamlined access to the aerial splice enclosure. Use with TAS120M and TAS120L ties for easy installation.
Short Description	Aerial Support Tie Spacer, PA66HIRHSUV, Black, 50/pkg
Global Part Name	TASPCR1-PA66HIRHSUV-BK
Length L (Imperial)	1.25
Length L (Metric)	31.8
Fixation Method	Others
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Outside Serrated
Width W (Imperial)	1.54
Width W (Metric)	39.1
Height H (Imperial)	0.89
Height H (Metric)	22.7

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	No
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Operating Temperature intermittent, 1000 hours	+320°F (+160°C)
Operating Temperature intermittent, 5000 hours	+257°F (+125°C)
Operating Temperature intermittent, 500 hours	+329°F (+165°C)
Reach Compliant (Article 33)	No
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)