

Specification Sheet

Part Number: 151-04727

Cradle holds wires along routing path while staging, allowing adjustments until ready to make permanent.

Optional "retention arms" version needs no cable tie to retain cables.

Unique EZ Feed slot maintains clear space to insert cable ties faster.

Built-in CutZone safety feature prevents damage to wires and cables when servicing.



Acrylic adhesive provides superior strength and longevity compared to many other adhesive options.

| | |
|----------------|--------------|
| Article Number | 151-04727 |
| Type | CTCM11CZA-AE |
| Color | White (WH) |
| Quantity Per | bag |

| | |
|---------------------|--|
| Product Description | This cradle mount with acrylic adhesive is fast and easy to apply to any flat surface and is ideal for routing wires in industrial applications where rework and adjustments are common. Mount features a 0.43" cradle opening enhanced with retention arms, providing temporary cable management for simple adjustments and cable additions, or final cable attachment with near-zero chance of disengagement. Cradle also protects against abrasion and cable damage. To permanently mount the bundle, the EZ Feed cable tie slot eliminates common obstructions for faster completion. During rework, the CutZone prevents wire damage when cutting off cable ties. |
| Short Description | Cradle Mount With Acrylic Adhesive, 0.43" Cradle Area w/ Retention Arms, PA66HS, White, 100/pkg |
| Global Part Name | CTCM11CZA-AE-PA66HS-WH |
| Length L (Imperial) | 1.23 |
| Length L (Metric) | 31.2 |
| Fixation Method | Screw Mounting and Adhesive |
| Width W (Imperial) | 0.93 |
| Width W (Metric) | 23.73 |
| Height H (Imperial) | 0.79 |
| Height H (Metric) | 20.1 |
| Material | Polyamide 6.6 heat stabilized (PA66HS) |

| | |
|--------------------------------|----------------------------------|
| Material Shortcut | PA66HS |
| Adhesive | High Bond Acrylic |
| Flammability | UL 94 V-2 (excluding adhesive) |
| Halogen Free | No |
| UV Resistant (Yes/No) | No |
| Adhesive Operating Temperature | -13°F to +158°F (-25°C to +70°C) |
| Operating Temperature | -13°F to +158°F (-25°C to +70°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| UL Recognized (US) | Yes |
| UL Recognized (US and Canada) | Yes |
| Package Quantity (Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909988 |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Privacy Policy](#)

[Cookie Policy](#)

[Terms and Conditions](#)