

## Specification Sheet

Part Number: 156-00590



Edge applications don't require additional fasteners or hole drilling.

Low push-on force reduces repetitive strain injuries.

Two-piece assembly allows mount to slide along strap, ensuring proper orientation.

2-Piece Cable Tie with Edge Clip, 8.0" Long, EC19, 3 - 6 mm Panel, 50lb, PA66UV/PA66HIRHSUV, Black, 100/pkg

Article Number 156-00590

Type T50REC19

Color Black (BK)

Quantity Per pack

Product Description HellermannTyton's Two-Piece Edge Clip with Cable Tie assemblies are designed specifically to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure, and the pull-off strength is high due to the integrated metal clamp that holds the edge clip in place.

Short Description 2-Piece Cable Tie with Edge Clip, 8.0" Long, EC19, 3 - 6 mm Panel, 50lb, PA66UV/PA66HIRHSUV, Black, 100/pkg

Global Part Name T50REC19-PA66UV/PA66HIRHS-BK

|                                     |                 |
|-------------------------------------|-----------------|
| Minimum Tensile Strength (Imperial) | 50              |
| Minimum Tensile Strength (Metric)   | 225             |
| Length L (Imperial)                 | 8.0             |
| Length L (Metric)                   | 202.0           |
| Fixation Method                     | Edge Clip       |
| Identification Plate Position       | none            |
| Variant                             | Inside Serrated |
| Width W (Imperial)                  | 0.18            |
| Width W (Metric)                    | 4.6             |
| Bundle Diameter Min (Imperial)      | 0.2             |
| Bundle Diameter Min (Metric)        | 5.0             |
| Bundle Diameter Max (Imperial)      | 1.97            |
| Bundle Diameter Max (Metric)        | 50.0            |
| Thickness T (Imperial)              | 0.05            |
| Thickness T (Metric)                | 1.2             |
| Height H (Imperial)                 | 0.05            |

|                                |  |
|--------------------------------|--|
| Height H (Metric)              | 1.2  |
| Panel Thickness Min (Imperial) | 0.12   |
| Panel Thickness Max (Imperial) | 0.24   |
| Panel Thickness Min (Metric)   | 3.0  |
| Panel Thickness Max (Metric)   | 6.0  |
| Material                       | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)<br>Polyamide 6.6 UV-stabilized (PA66UV) |
| Foot Part Material             | PA66HIRHSUV  |
| Material Shortcut              | PA66UV PA66HIRHS   |
| Material Cable Tie             | Polyamide 6.6 UV-stabilized (PA66UV)   |
| Flammability                   | UL 94 HB   |
| UV Resistant (Yes/No)          | Yes  |
| Use Conditions                 | For Indoor and Outdoor Use   |
| Operating Temperature          | -40°F to +230°F (-40°C to +110°C) -40°F to +185°F (-40°C to +85°C)                                       |
| Reach Compliant (Article 33)   | Yes  |
| ROHS Compliant                 | Yes  |

|                             |            |
|-----------------------------|------------|
| Package Quantity (Imperial) | 100        |
| Package Quantity (Metric)   | 100        |
| Customs Number              | 3926909988 |

7930 N. Faulkner Road, Milwaukee, WI 53224  
Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)