

Specification Sheet

Part Number: 156-01096

High tensile strength delivers reliable performance for heavy duty applications.

Low-profile design allows for mount to be placed in areas where space is limited.

A suitable alternative for metal clamps.

Robust design withstands vibration and displacement forces.

Metal bushing provides high tightening torque.



2-Piece Cable Tie with Screw Mount, 14.5"L, 0.24" Hole, 3.94" Max Bundle Dia, 120 lb, PA66HIRHS/PA66UV, Black, 200/pkg

Article Number

156-01096

Type

X120RDHDM6

Color

Black (BK)

Quantity Per

pack

Product Description

Multi-piece heavy duty dual clamp ties provide parallel separation between high-voltage cables to protect them from abrasion. A variety of mounting hole options are available for securing bundles along the chassis or body of today's electric vehicles.

Short Description

2-Piece Cable Tie with Screw Mount, 14.5"L, 0.24" Hole, 3.94" Max Bundle Dia, 120 lb, PA66HIRHS/PA66UV, Black, 200/pkg

Global Part Name X120RDHDM6-PA66HIRHS/PA66UV-BK

Minimum Tensile Strength (Imperial) 120

Minimum Tensile Strength (Metric) 535

Length L (Imperial) 14.53

Length L (Metric) 369.0

Fixation Method Screw Mounting and Rivet

Identification Plate Position none

Tie Closure plastic pawl

Width W (Imperial) 0.30

Width W (Metric) 7.7

Bundle Diameter Min (Imperial) 0.39

Bundle Diameter Min (Metric) 10.0

Bundle Diameter Max (Imperial) 3.94

Bundle Diameter Max (Metric) 100.0

Thickness T (Metric) 1.6

Height H (Imperial) 0.61

Height H (Metric)	15.5
Mounting Hole Diameter D (Imperial)	0.24 "
Mounting Hole Diameter D (Metric)	6.2 mm
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 UV-resistant (PA66UV)
Foot Part Material	PA66UV
Material Shortcut	PA66HIRHS PA66UV
Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	200
Package Quantity (Metric)	200
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)