

Specification Sheet

Part Number: 156-01640

2-Piece assembled fir tree cable tie secures bundles running perpendicular to 9x17 oval mounting hole.

Updated 9x17 mm oval fir tree design maintains bundle orientation.

Fir tree provides low insertion force with high extration resistance, for easy assembly and reliable performance.

Disc feature prevents rattling in high-vibration applicatiосn and protects against debris ingress.



2-Piece Cable Tie with Oval Fir Tree Mount, 8.0" Long, 9.0 x 17.0 mm Mounting Hole, 50lb, PA66HIRHSUV, Black, 500/bag

Article Number 156-01640

Type T50RFT9X17A2

Color Black (BK)

Quantity Per pack

Product Description

These two-piece fasteners are pre-assembled and offer a simple and versatile method of bundling and mounting cables. The fir tree base will easily push into pre-punched holes in panels or threaded blind holes and offers a secure fit. The two-piece design enables the head of the tie to be oriented to the required position to ease assembly, while the disc on top of the fir tree covers the hole and minimizes the ingress of water and dirt.

| | |
|-------------------------------------|---|
| Short Description | 2-Piece Cable Tie with Oval Fir Tree Mount, 8.0" Long, 9.0 x 17.0 mm Mounting Hole, 50lb, PA66HIRHSUV, Black, 500/bag |
| Global Part Name | T50RFT9X17A2-PA66HIRHSUV-BK |
| Minimum Tensile Strength (Imperial) | 50 |
| Minimum Tensile Strength (Metric) | 225 |
| Length L (Imperial) | 8.0 |
| Length L (Metric) | 203.2 |
| Fixation Method | Fir tree for round holes |
| Identification Plate Position | none |
| Tie Closure | plastic pawl |
| Width W (Imperial) | 0.18 |
| Width W (Metric) | 4.6 |
| Bundle Diameter Min (Imperial) | 0.2 |
| Bundle Diameter Min (Metric) | 5.0 |
| Bundle Diameter Max (Imperial) | 1.97 |
| Bundle Diameter Max (Metric) | 50.0 |
| Panel Thickness Min (Imperial) | 0.02 |

| | |
|---------------------------------------|--|
| Panel Thickness Max (Imperial) | 0.22 |
| Panel Thickness Min (Metric) | 0.6 |
| Panel Thickness Max (Metric) | 5.5 |
| Mounting Hole Diameter D (Imperial) | 0.35 x 0.67 " |
| Mounting Hole Diameter D (Metric) | 9.0 x 17.0 mm |
| Mounting Hole Diameter D Max (Metric) | 17.0 |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Foot Part Material | PA66HIRHSUV |
| Material Shortcut | PA66HIRHSUV |
| UV Resistant (Yes/No) | Yes |
| Use Conditions | For Indoor and Outdoor Use |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)