

## Specification Sheet

Part Number: 156-02380

Once installed, perpendicular arrowhead arms reduce movement and will not collapse when exposed to water or load

Integrated dual seal meets IP65 for protection against water, dust, chemicals, air and sound

15 mm and 25 mm offset designs fasten bundles away from obstructions, heat or sources of abrasion

Superior design and high-spec materials maintain routing position to deliver consistent performance in the most rugged applications

Low-profile design saves 5 mm of height when installed

All ties rated to 222 N (50 lb) tensile strength to ensure long-term bundling reliability

Sealed arrowhead meets USCAR44 push in, pull off and sealing standards



2-Piece Cable Tie with Arrowhead Mount with Seal, 1.2 - 1.8mm panel, 6.5mm/6.35mm HEX, PA66HS/TPE, Black/Gray, 2000/ctn

|                |                      |
|----------------|----------------------|
| Article Number | 156-02380            |
| Type           | T50RSRAH6.5D1.4TSD   |
| Color          | Black (BK) Gray (GY) |
| Quantity Per   | bag                  |

|                                     |  |
|-------------------------------------|--|
| Product Description                 | HellermannTyton sealed clips and ties are constructed of engineered nylon with a dual TPE (thermo plastic elastomer) seal. The combination of dual seal and engineered arrowhead provide superior sealing performance for applications where protection from moisture and debris is essential. |
| Short Description                   | 2-Piece Cable Tie with Arrowhead Mount with Seal, 1.2 - 1.8mm panel, 6.5mm/6.35mm HEX, PA66HS/TPE, Black/Gray, 2000/ctn  |
| Global Part Name                    | T50RSRAH6.5D1.4TSD-PA66HS/TPE-BK/GY  |
| Minimum Tensile Strength (Imperial) | 50   |
| Minimum Tensile Strength (Metric)   | 225  |
| Length L (Imperial)                 | 8.0  |
| Length L (Metric)                   | 202.0  |
| Fixation Method                     | Arrowhead  |
| Identification Plate Position       | none   |
| Releasable Closure                  | No   |
| Tie Closure                         | plastic pawl   |
| Variant                             | Inside Serrated  |
| Width W (Imperial)                  | 0.87   |
| Width W (Metric)                    | 22.3   |

|   |                            |
|---|----------------------------|
| Bundle Diameter Min (Imperial)          | 0.12                       |
| Bundle Diameter Min (Metric)            | 3.0                        |
| Bundle Diameter Max (Imperial)          | 1.97                       |
| Bundle Diameter Max (Metric)            | 50.0                       |
| Height H (Imperial)                     | .59                        |
| Height H (Metric)                       | 15.08                      |
| Panel Thickness Min (Imperial)          | 0.05                       |
| Panel Thickness Max (Imperial)          | 0.07                       |
| Panel Thickness Min (Metric)            | 1.2                        |
| Panel Thickness Max (Metric)            | 1.8                        |
| Mounting Hole Diameter D (Imperial)     | 0.25 (hexagonal) ";0.26    |
| Mounting Hole Diameter D (Metric)       | 6.35 mm (hexagonal) 6.5 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.25                       |
| Mounting Hole Diameter D Max (Imperial) | 0.26                       |
| Mounting Hole Diameter D Max (Metric)   | 6.5                        |
| Disc Diameter (Metric)                  | 22,3                       |

|                             |  |
|-----------------------------|--|
| Material                    | Thermoplastic Elastomer (TPE) Polyamide 6.6 heat stabilized (PA66HS) |
| Foot Part Material          | TPE  |
| Material Shortcut           | TPE PA66HS   |
| Material Cable Tie          | Polyamide 6.6 heat stabilized (PA66HS)                               |
| UV Resistant (Yes/No)       | No   |
| Use Conditions              | For Indoor and Outdoor Use   |
| Operating Temperature       | -40°F to +257°F (-40°C to +125°C)                                    |
| ROHS Compliant              | Yes  |
| Package Quantity (Imperial) | 2000   |
| Package Quantity (Metric)   | 2000   |
| Customs Number              | 3926909988   |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)