

## Specification Sheet

Part Number: 156-02467

Once installed, perpendicular arrowhead arms reduce movement and will not collapse when exposed to water or load

Integrated dual seal meets IP65 for protection against water, dust, chemicals, air and sound

15 mm and 25 mm offset designs fasten bundles away from obstructions, heat or sources of abrasion

Superior design and high-spec materials maintain routing position to deliver consistent performance in the most rugged applications

Low-profile design saves 5 mm of height when installed

All ties rated to 222 N (50 lb) tensile strength to ensure long-term bundling reliability

Sealed arrowhead meets USCAR44 push in, pull off and sealing standards



2-Piece Cable Tie with Arrowhead Mount with Seal, 1.2 - 1.8mm panel, 6.5mm/6.35mm HEX, PA66HIRHSUV, Black/Gray, 2000/ctn

Article Number	156-02467
Type	T50ROS15ACCSRAH1.4T
Color	Black (BK) Gray (GY)
Quantity Per	bag

Product Description	HellermannTyton sealed clips and ties are constructed of engineered nylon with a dual TPE (thermo plastic elastomer) seal. The combination of dual seal and engineered arrowhead provide superior sealing performance for applications where protection from moisture and debris is essential.
Short Description	2-Piece Cable Tie with Arrowhead Mount with Seal, 1.2 - 1.8mm panel, 6.5mm/6.35mm HEX, PA66HIRHSUV, Black/Gray, 2000/ctn
Global Part Name	T50ROS15ACCSRAH1.4T-PA66HIRHSUV/TPE-BK/GY
Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	8.58
Length L (Metric)	218
Offset Length (Imperial)	0.59
Offset Length (Metric)	15.0
Fixation Method	Arrowhead
Identification Plate Position	none
Tie Closure	plastic pawl
Width W (Imperial)	1.11
Width W (Metric)	28.4

Bundle Diameter Min (Imperial)	0.08
Bundle Diameter Min (Metric)	2.0
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	0.728
Height H (Metric)	18.5
Panel Thickness Min (Imperial)	0.05
Panel Thickness Max (Imperial)	0.07
Panel Thickness Min (Metric)	1.2
Panel Thickness Max (Metric)	1.8
Mounting Hole Diameter D (Imperial)	0.25 (hexagonal) ";0.26
Mounting Hole Diameter D (Metric)	6.5 mm 6.35 mm (hexagonal)
Mounting Hole Diameter D Min (Imperial)	0.25
Mounting Hole Diameter D Max (Imperial)	0.26
Mounting Hole Diameter D Max (Metric)	6.5
Disc Diameter (Metric)	22.3

Material	Thermoplastic Elastomer (TPE) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	TPE PA66HIRHSUV
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	2200
Package Quantity (Metric)	2200
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)