

## Specification Sheet

Part Number: 156-02873



Edge Clip attaches easily to plastic and metal sheets without the need for a mounting hole.

The 360-degree locking enclosure dynamically fits a range of bundle sizes.

Clamp can be opened for bundle maintenance.

Independent rotation allows for adjustable routing orientation.

Edge Clip to LOC Locking Clamp, 20-25mm Clamp, 1-3mm Panel, PA66HIRHSUV/PA66HIRHSUVR5, Blk, 2000/Ctn

Article Number	156-02873
Type	ECF90LOC20-25
Color	Black (BK)
Quantity Per	bag
Product Description	The LOC with edge clip mount features HellermannTyton's self-adjusting, locking bundle clamp. The clip is easy to secure, and the extraction force is high due to the integrated metal clamp that holds the edge clip in place.
Short Description	Edge Clip to LOC Locking Clamp, 20-25mm Clamp, 1-3mm Panel, PA66HIRHSUV/PA66HIRHSUVR5, Blk, 2000/Ctn

Global Part Name ECF90LOC20-25-PA66HIRHSUVR5/PA66HIRHSUV-BK

Length L (Imperial) 1.53

Length L (Metric) 38.91

Fixation Method Edge Clip

Width W (Imperial) 0.47

Width W (Metric) 12.0

Bundle Diameter Min (Imperial) 0.79

Bundle Diameter Min (Metric) 20.0

Bundle Diameter Max (Imperial) 0.98

Bundle Diameter Max (Metric) 25.0

Height H (Imperial) 2.88

Height H (Metric) 73.2

Depth D (Imperial) 0.55

Depth D (Metric) 14.0

Panel Thickness Min (Imperial) 0.04

Panel Thickness Max (Imperial) 0.12

Panel Thickness Min (Metric) 1.0

Panel Thickness Max (Metric) 3.0

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Polyamide 6.6, high impact modified, heat and UV-stabilized, proprietary blend (PA66HIRHSUVR5)

Material Shortcut PA66HIRHSUV PA66HIRHSUVR5

Flammability UL 94 HB

UV Resistant (Yes/No) Yes

Use Conditions For Indoor and Outdoor Use

ROHS Compliant Yes

Package Quantity (Imperial) 1000

Package Quantity (Metric) 1000

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.