

Specification Sheet

Part Number: 156-02916

Multi option stud mount clip secures bundles running alongside a bolt or stud.

Patented retention design features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.

Controlled flex and angled entry promote easy installation.

Independent rotation allows for adjustable routing orientation.

High-performance stud mount design allows for easy installation and delivers outstanding stud retention to keep bundles secure.



Stud Mount to MOC Clip, 22mm Clip, 5mm/6mm Stud Mount, PA66HIRHSUV, Black, 1000/ctn

Article Number	156-02916
----------------	-----------

Type	SMF2MOC22M
------	------------

Color	Black (BK)
-------	------------

Quantity Per	pack
--------------	------

Product Description	The MOC with stud mount features HellermannTyton's unique retention clip with a best-in-class stud mount to secure to a 5mm or 6mm stud or bolt. The mount delivers a low insertion force while exhibiting high extraction resistance for a secure mounting point.
---------------------	--

Short Description	Stud Mount to MOC Clip, 22mm Clip, 5mm/6mm Stud Mount, PA66HIRHSUV, Black, 1000/ctn
Global Part Name	SMF2MOC22M-PA66HIRHSUV-BK
Length L (Imperial)	2.23
Length L (Metric)	56.6
Fixation Method	Stud Mount
Bundle Diameter Min (Imperial)	0.79
Bundle Diameter Min (Metric)	20.0
Bundle Diameter Max (Imperial)	0.98
Bundle Diameter Max (Metric)	25.0
Height H (Imperial)	1.54
Height H (Metric)	39.2
Depth D (Imperial)	0.61
Depth D (Metric)	15.5
Mounting Hole Diameter D (Metric)	6.0 mm 5.0 mm
Stud Diameter (Metric)	6.0 mm 5.0 mm
Stud Diamater (Imperial)	0.20 ";0.24

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)