

Specification Sheet

Part Number: 156-03136


PAEK material provides exceptional heat resistance, withstanding temperatures up to 200° C (392° F).

Offers outstanding chemical resistance against hydrocarbons.

PAEK material has double the tensile strength of nylon.

Friction tab inside fir tree retains tie in mount to aid in installation.

Disc feature prevents rattling in high-vibration applications and protects against debris ingress.



2-Piece Cable Tie with Fir Tree Mount, 7.9"L, 0.18 - 0.20" Mounting Hole, 100lb, PAEK, Beige, 2000/ctn

Article Number 156-03136

Type PAT100LSDFT5

Color Beige (BGE)

Quantity Per carton

Product Description HellermannTyton's fir tree mounts provide a secure grip in a mounting hole. The mount can slide along the cable tie to adjust orientation as needed. Fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.

Short Description	2-Piece Cable Tie with Fir Tree Mount, 7.9"L, 0.18 - 0.20" Mounting Hole, 100lb, PAEK, Beige, 2000/ctn
Global Part Name	PAT100LSDFT5-PAEK-BGE
Minimum Tensile Strength (Imperial)	100
Minimum Tensile Strength (Metric)	445
Length L (Imperial)	7.9
Length L (Metric)	200.6
Fixation Method	Fir Tree
Identification Plate Position	none
Tie Closure	plastic pawl
Width W (Imperial)	0.16
Width W (Metric)	4.0
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.4
Bundle Diameter Max (Metric)	35.0
Thickness T (Imperial)	0.06

Thickness T (Metric)	1.5
Height H (Imperial)	0.70
Height H (Metric)	17.8
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.14
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	3.5
Mounting Hole Diameter D (Imperial)	0.18 - 0.20
Mounting Hole Diameter D (Metric)	M6 Threaded 4.5 - 5.0 mm
Mounting Hole Diameter D Min (Imperial)	0.18
Mounting Hole Diameter D Max (Imperial)	0.20
Mounting Hole Diameter D Max (Metric)	5.0
Disc Diameter (Metric)	19.6
Disc Diameter (Imperial)	0.78
Material	Polyaryletherketone (PAEK)

Material Shortcut	PAEK
Use Conditions	For Indoor Use Only
Operating Temperature	-67°F to +392°F (-55°C to +200°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	2000
Package Quantity (Metric)	2000
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)