

Specification Sheet

Part Number: 156-03182



Triple routing tie mount separator for up to three 25 mm routings.

Keep routings separated with center-to-center distance of 28 mm.

Preassembled cable tie on bracket for easier installation.

2-Piece Triple Bracket Separator, Outside Serrated 120 lb Tie, 0.98" Max Dia., PA66HIRHSUV, Blk, 250/ctn

Article Number	156-03182
Type	T120Triple25
Color	Black (BK)
Quantity Per	carton
Product Description	Keeps bundles separated and aids routing three lines parallel to one another.
Short Description	2-Piece Triple Bracket Separator, Outside Serrated 120 lb Tie, 0.98" Max Dia., PA66HIRHSUV, Blk, 250/ctn
Global Part Name	T120TRIPLE25-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)	120
Minimum Tensile Strength (Metric)	535
Length L (Imperial)	3.78
Length L (Metric)	96.0
Identification Plate Position	none
Width W (Imperial)	1.15
Width W (Metric)	29.0
Bundle Diameter Max (Imperial)	0.98
Bundle Diameter Max (Metric)	25
Bundle Diameter 1st Loop Max (Imperial)	0.98
Bundle Diameter 1st Loop Max (Metric)	25
Bundle Diameter 2nd Loop Max (Imperial)	0.98
Bundle Diameter 2nd Loop Max (Metric)	25
Height H (Imperial)	1.46
Height H (Metric)	37.0

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Foot Part Material	PA66HIRHSUV
Material Shortcut	PA66HIRHSUV
Material Cable Tie	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	250
Package Quantity (Metric)	250
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)