

Specification Sheet

Part Number: 156-03194

Bolt-down, one-piece design can bundle and secure two high-voltage cables inside convoluted tubing.

Saddle with wide strap tie for third routing option.

Integrated M6 Stud Mount acts as third hand for retention while attaching.



2-Pc P-Clamp, Dual Routing, M6 Mount, Assembled Wide Strap, 0.98" Max Dia., PA66HRHSUV, Blk, 250/ctn

Article Number	156-03194
Type	WSSDHVC24M6SD
Color	Black (BK)
Quantity Per	carton
Product Description	This two-piece locking clamp and wide strap tie assembly replaces an expensive four-piece solution consisting of a metal bracket, EPDM isolator, tie and stud retainer. The wide strap cable tie offers a third bundle routing option.
Short Description	2-Pc P-Clamp, Dual Routing, M6 Mount, Assembled Wide Strap, 0.98" Max Dia., PA66HRHSUV, Blk, 250/ctn
Global Part Name	WSSDHVC24M6SD-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)	120
Minimum Tensile Strength (Metric)	535
Length L (Imperial)	4.48
Length L (Metric)	113.9
Fixation Method	Stud Mount
Identification Plate Position	none
Width W (Imperial)	1.20
Width W (Metric)	30.5
Bundle Diameter Max (Imperial)	0.98
Bundle Diameter Max (Metric)	25.0
Bundle Diameter 1st Loop Max (Imperial)	0.98
Bundle Diameter 1st Loop Max (Metric)	25.0
Bundle Diameter 2nd Loop Max (Imperial)	0.98
Bundle Diameter 2nd Loop Max (Metric)	25.0
Height H (Imperial)	1.24
Height H (Metric)	31.5

Mounting Hole Diameter D (Imperial)	0.24 "
Mounting Hole Diameter D (Metric)	M6 x 1
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Foot Part Material	PA66HIRHSUV
Material Shortcut	PA66HIRHSUV
Material Cable Tie	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	250
Package Quantity (Metric)	250
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)