

Specification Sheet

Part Number: 156-03366

Pre-assembled 2-piece fixing tie with coupler

Cable tie head can be moved after bundling

Easy addition of cables after assembly

For parallel routing of bundles that can be twisted 90° even after installation



3-Piece Wide Strap Tie with Coupler, 15" Long, 0.39 - 4.13" Dia, 120lbs, PA66HIRHS, Black, 100/bag

Article Number 156-03366

Type T120RCOUPLER

Color Black (BK)

Quantity Per pack

Product Description

The Coupler is the simple way to connect two cable ties for a parallel routing of two bundles. This special design allows the ties 90 degrees of rotation. This is ideal for all applications where the cable, pipe or hose should move flexible in relation to the fixing point. The Coupler can be used with one or two cable ties. This allows easily subsequent installation or replacements of further cables, pipes or hose.

Short Description

3-Piece Wide Strap Tie with Coupler, 15" Long, 0.39 - 4.13" Dia, 120lbs, PA66HIRHS, Black, 100/bag

Global Part Name

T120RCOUPLER-PA66HIRHS-BK

Minimum Tensile Strength (Imperial)

120

Minimum Tensile Strength (Metric)

535

Length L (Imperial)

14.96

Length L (Metric)

390.0

Identification Plate Position

none

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.30

Width W (Metric)

7.6

Bundle Diameter Min (Imperial)

0.39

Bundle Diameter Min (Metric)

10.0

Bundle Diameter Max (Imperial)

4.13

Bundle Diameter Max (Metric)

105.0

Bundle Diameter 1st Loop Max (Imperial)

3.937

Bundle Diameter 1st Loop Max (Metric)

100.0

Bundle Diameter 2nd Loop Max (Imperial)	3.937
Bundle Diameter 2nd Loop Max (Metric)	100.0
Height H (Imperial)	0.59
Height H (Metric)	14.9
Cable Tie Width Max (Imperial)	0.3
Cable Tie Width Max (Metric)	7.62
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Foot Part Material	PA66HIRHS
Material Shortcut	PA66HIRHS
Material Cable Tie	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Flammability	UL 94 HB
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	100

Package Quantity (Metric) 100

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)