

Specification Sheet

Part Number: 156-03950

Robust fir tree design provides low insertion effort yet delivers exceptional retention strength.

Anti-rotational oval fir tree keeps bundle in intended direction.

Standoff raises bundle 14.8 mm above mounting hole to protect it from rubbing, heat or obstructions.

Heavy duty T120 tie provides 120 lb (534 N) tensile strength to secure bundles up to 4" (104 mm).

Friction tab inside fir tree allows the tie to sit in mount without falling out prior to installation.



3-Piece Cable Tie with Oval Fir Tree Standoff Mount, Unassembled, 15"L, 12x17mm Hole, PA66HIRHSUV, Black, 500/ctn

Article Number 156-03950

Type T120R2xDHVSDOS12x17

Color Black (BK)

Quantity Per pack

Product Description HellermannTyton's Fir Tree Mounts provide a secure grip in a mounting hole. The mount can slide along the cable tie to adjust orientation as needed. They are optimized for up to 3-to-1 extraction versus insertion force to make assembly fast and easy. These mounts are sold unassembled.

Short Description	3-Piece Cable Tie with Oval Fir Tree Standoff Mount, Unassembled, 15"L, 12x17mm Hole, PA66HIRHSUV, Black, 500/ctn
Global Part Name	T120R2xDHVSDOS12x17-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	120
Minimum Tensile Strength (Metric)	535
Length L (Imperial)	8.0
Length L (Metric)	203.2
Fixation Method	Fir Tree for oval holes
Variant	Inside Serrated
Width W (Imperial)	1.26
Width W (Metric)	32
Bundle Diameter Min (Imperial)	0.2
Bundle Diameter Min (Metric)	5.0
Bundle Diameter Max (Imperial)	4.13
Bundle Diameter Max (Metric)	105.0
Height H (Imperial)	1.24
Height H (Metric)	31.6

Cable Tie Width Max (Imperial)	0.30
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.19
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	4.73
Mounting Hole Diameter D (Imperial)	0.47 x 0.67 "
Mounting Hole Diameter D (Metric)	12.0 x 17.0 mm
Mounting Hole Diameter D Min (Imperial)	0.47 x 0.67
Mounting Hole Diameter D Max (Imperial)	0.47 x 0.67
Mounting Hole Diameter D Max (Metric)	17.4
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Foot Part Material	PA66HIRHSUV
Material Shortcut	PA66HIRHSUV
Material Cable Tie	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Flammability	UL 94 HB

Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)