

## Specification Sheet

Part Number: 156-04062



Pre-assembled self-affixing tie with coupler.

Cable tie head can be moved after bundling.

Easy addition of cables after assembly.

For parallel routing of bundles that can be twisted 90° even after installation.

3-Piece T50R Tie with Coupler, 8" Long, 0.08 - 1.97" Dia, 50lbs, PA66HIRHS/PA66HIRHSUV, Orange/Black, 500/pkg

Article Number 156-04062

Type T50RCOUPLER

Color Black (BK) Orange (OG), High Voltage (HV)

Quantity Per pack

**Product Description**  
The Coupler is the simple way to connect two cable ties for a parallel routing of two bundles. His special design allows the ties 90 degrees of rotation. This is ideal for all applications where the cable, pipe or hose should move flexible in relation to the fixing point. The Coupler can be used with one or two cable ties. This allows easily subsequent installation or replacements of further cables, pipes or hose.

**Short Description**  
3-Piece T50R Tie with Coupler, 8" Long, 0.08 - 1.97" Dia, 50lbs, PA66HIRHS/PA66HIRHSUV, Orange/Black, 500/pkg

Global Part Name

T50RCOUPLER-PA66HIRHS/PA66HIRHSUV-OG/BK

Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	7.874
Length L (Metric)	202.0
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.08
Bundle Diameter Min (Metric)	2.0
Bundle Diameter Max (Imperial)	1.85
Bundle Diameter Max (Metric)	47.0
Bundle Diameter 1st Loop Max (Imperial)	1.97

Bundle Diameter 1st Loop Max (Metric)	50.0
Bundle Diameter 2nd Loop Max (Imperial)	1.97
Bundle Diameter 2nd Loop Max (Metric)	50.0
Height H (Imperial)	0.33
Height H (Metric)	8.3
Cable Tie Width Max (Imperial)	0.18
Cable Tie Width Max (Metric)	4.70
Disc Diameter (Imperial)	0.47

Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
----------	--

Foot Part Material	PA66HIRHSUV
--------------------	-------------

Material Shortcut	PA66HIRHSUV PA66HIRHS
-------------------	-----------------------

Flammability	UL 94 HB
--------------	----------

Halogen Free	Yes
--------------	-----

UV Resistant (Yes/No)	Yes
-----------------------	-----

Use Conditions	For Indoor and Outdoor Use
----------------	----------------------------

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)