

## Specification Sheet

Part Number: 156-04068

Pre-assembled 2-piece fixing tie with fir tree foot part.


Cable tie head can be moved after bundling.

Easy to assemble without the need for a tool.

Disc adjusts tie for pressure from various directions and minimises access of dust and dirt.

Fir tree foot part can be used for a variety of panel thicknesses.

Suitable for use within threaded holes.



Dual Cable Ties with Oval Fir Tree, 8"L, 6.2 x 12.2 mm;6.5 x 12.5 mm;6.5 x 13.0 mm or 7.0 x 12.0 mm Mounting Hole, PA66HIRHS/UV, BK/OG, 500/ctn

|                |   |
|----------------|---|
| Article Number | 156-04068                                 |
| Type           | T50RX2DUALSDFTOCCA                        |
| Color          | Black (BK) Orange (OG), High Voltage (HV) |
| Quantity Per   | pack                                      |

|                                     |  |
|-------------------------------------|--|
| Product Description                 | These two-piece self-affixing cable ties are supplied ready assembled and offer a simple and versatile method of bundling and fastening cables. The deep-hole anchor will easily push into blind holes with or without thread and offers a very secure attachment. The two-piece design enables the head of the tie to be oriented to the required position to ease assembly, while the disc on the top of the fir tree covers the hole and minimizes the ingress of water and dirt. |
| Short Description                   | Dual Cable Ties with Oval Fir Tree, 8"L, 6.2 x 12.2 mm;6.5 x 12.5 mm;6.5 x 13.0 mm or 7.0 x 12.0 mm Mounting Hole, PA66HIRHS/UV, BK/OG, 500/ctn  |
| Global Part Name                    | T50RX2DUALSDFTOCCA-PA66HIRHS/PA66HIRHSUV-OG/BK   |
| Minimum Tensile Strength (Imperial) | 50   |
| Minimum Tensile Strength (Metric)   | 225  |
| Length L (Imperial)                 | 8.0  |
| Length L (Metric)                   | 203.2  |
| Fixation Method                     | Fir Tree for oval holes  |
| Identification Plate Position       | none   |
| Releasable Closure                  | No   |
| Tie Closure                         | plastic pawl   |
| Width W (Imperial)                  | 1.10   |
| Width W (Metric)                    | 28.0   |

|                                     |   |
|-------------------------------------|---|
| Bundle Diameter Min (Imperial)      | 0.06  |
| Bundle Diameter Min (Metric)        | 1.5   |
| Bundle Diameter Max (Imperial)      | 1.97  |
| Bundle Diameter Max (Metric)        | 50.0  |
| Thickness T (Imperial)              | 0.05  |
| Thickness T (Metric)                | 1.2   |
| Cable Tie Head Length (Imperial)    | 0.29  |
| Cable Tie Head Width (Imperial)     | 0.3   |
| Height H (Imperial)                 | 0.86  |
| Height H (Metric)                   | 21.9  |
| Cable Tie Width Max (Imperial)      | 0.21  |
| Panel Thickness Min (Imperial)      | 0.02  |
| Panel Thickness Max (Imperial)      | 0.26  |
| Panel Thickness Min (Metric)        | 0.6   |
| Panel Thickness Max (Metric)        | 6.75  |
| Mounting Hole Diameter D (Imperial) | 0.28 x 0.47 " 0.26 x 0.51 " 0.26 x 0.49 " 0.24 x 0.48 " |
| Mounting Hole Diameter D (Metric)   | 7.0 x 12.0 mm 6.2 x 12.2 mm 6.5 x 12.5 mm 6.5 x 13.0 mm |

Mounting Hole Diameter D Min (Imperial) 0.24

Mounting Hole Diameter D Max (Imperial) 0.51

Mounting Hole Diameter D Max (Metric) 7.0

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)  
Polyamide 6.6 high impact modified, heat and UV stabilized  
(PA66HIRHSUV)

Foot Part Material PA66HIRHSUV

Material Shortcut PA66HIRHSUV PA66HIRHS

Material Cable Tie Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Flammability UL 94 HB

Halogen Free Yes

UV Resistant (Yes/No) Yes

Use Conditions For Indoor and Outdoor Use

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)