

Specification Sheet

Part Number: 157-00342



Low-profile head allows mounts to stack, providing more mounting versatility from a single stud.

Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure.

Low Profile M10 Stud Mount Tie, 7.5" Tie, 80lb Tensile Strength, PA66HIRHSUV, Black, 2500/pkg

Article Number 157-00342

Type T80ROSLPSB10U

Color Black (BK)

Quantity Per pack

Product Description One-piece mounting ties offer a complete solution by both bundling cable and at the same time providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.

Short Description Low Profile M10 Stud Mount Tie, 7.5" Tie, 80lb Tensile Strength, PA66HIRHSUV, Black, 2500/pkg

Global Part Name T80ROSLPSB10U-PA66HIRHSUV-BK

| | |
|-------------------------------------|--------------|
| Minimum Tensile Strength (Imperial) | 80 |
| Minimum Tensile Strength (Metric) | 355 |
| Length L (Imperial) | 8.5 |
| Length L (Metric) | 215.9 |
| Fixation Method | Stud Mount |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Width W (Imperial) | 0.82 |
| Width W (Metric) | 20.8 |
| Bundle Diameter Min (Imperial) | 0.14 |
| Bundle Diameter Min (Metric) | 3.5 |
| Bundle Diameter Max (Imperial) | 1.97 |
| Bundle Diameter Max (Metric) | 50.0 |
| Cable Ties | 157-00342 |
| Height H (Imperial) | 0.28 |

| | |
|-------------------------------------|--|
| Height H (Metric) | 7.0 |
| Mounting Hole Diameter D (Imperial) | 0.39 x 0.06 |
| Mounting Hole Diameter D (Metric) | M10 x 1.5 |
| Stud Diameter (Metric) | 10.0 mm |
| Stud Diameter (Imperial) | 0.39 |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV |
| Flammability | UL 94 HB |
| Halogen Free | Yes |
| UV Resistant (Yes/No) | Yes |
| Use Conditions | For Indoor and Outdoor Use |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |

Package Quantity (Imperial) 2500

Package Quantity (Metric) 2500

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)