


Specification Sheet

Part Number: 157-04136



All-in-one bundling and fastening solution reduces costs and assembly time.

Variety of fir tree diameters and offset lengths address most offset applications.

High-spec materials and superior design deliver excellent performance and value.

1-Piece Cable Tie with Offset Fir Tree, 8.5" Long, 50 lb Tensile Strength, PA46, Gray, 500/bag

Article Number 157-04136

Type T50ROSFTM6SO12.5B

Color Gray (GY)

Quantity Per bag

Product Description Offset cable ties route and position bundles away from a mounting hole. Rigid offset bar eliminates potential bending of wire or cables once installed. Multiple offset distances and fir tree sizes cover the majority of industry offset applications. The tie strap's outside serration design provides a smooth surface to protect soft bundles. HellermannTyton's one-piece mounting ties offer a complete solution by both bundling and mounting. Their ideal combination of high-specification materials and superior design suit the needs of complex applications.

Short Description 1-Piece Cable Tie with Offset Fir Tree, 8.5" Long, 50 lb Tensile Strength, PA46, Gray, 500/bag

Global Part Name T50ROSFTM6SO12.5B-PA46-GY

Minimum Tensile Strength (Imperial) 50

Minimum Tensile Strength (Metric) 225

Length L (Imperial) 8.5

Length L (Metric) 215.5

Offset Length (Imperial) 0.49

Offset Length (Metric) 12.5

Fixation Method Fir tree for round holes

Identification Plate Position none

Releasable Closure No

Width W (Imperial) 0.19

Width W (Metric) 4.7

Bundle Diameter Min (Imperial) 0.08

Bundle Diameter Min (Metric) 2.0

Bundle Diameter Max (Imperial) 1.97

Bundle Diameter Max (Metric) 50.0

| | |
|-------------------------------------|----------------------|
| Panel Thickness Min (Imperial) | 0.02 |
| Panel Thickness Max (Imperial) | 0.26 |
| Panel Thickness Min (Metric) | 0.5 |
| Panel Thickness Max (Metric) | 6.65 |
| Mounting Hole Diameter D (Imperial) | 0.24 |
| Mounting Hole Diameter D (Metric) | M6 |
| Material | Polyamide 4.6 (PA46) |
| Material Shortcut | PA46 |
| Flammability | UL 94 V-2 |
| Halogen Free | Yes |
| Use Conditions | For Indoor Use Only |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 500 |
| Package Quantity (Metric) | 500 |
| Customs Number | 3926909988 |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)