

## Specification Sheet

Part Number: 170-03217

Split wrap design needs no fasteners and installs quickly, saving assembly time and future accessibility without disassembly.

Bends to a tight radius without distortion or splitting open.

Unique construction retains shape and rigidity throughout unrolling.

Added flame-inhibitor fibers extinguish quickly and reduces potential flame spread to surrounding components.

Easy open design allows quick access and ability to apply protective sleeving post assembly or post installation situations.



Braided Sleeving, Split Wrap Woven, Flame Retardant, 3/8" Dia, PET, Black, 250 ft/bulk reel

|                |             |
|----------------|-------------|
| Article Number | 170-03217   |
| Type           | BSSWVFR380B |
| Color          | Black (BK)  |
| Quantity Per   | pack        |

|                                |   |
|--------------------------------|---|
| Product Description            | A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires. More flexible than spiral wraps or convoluted tubing, this product is a fast and easy option for adding protection in post-assembly or post-installation applications. Meets NFPA 130 rail market applications. |
| Short Description              | Braided Sleeving, Split Wrap Woven, Flame Retardant, 3/8" Dia, PET, Black, 250 ft/bulk reel   |
| Global Part Name               | BSSWVFR380B-PET-BK  |
| Length L (Imperial)            | 250.0   |
| Length L (Metric)              | 76.2  |
| Bundle Diameter Min (Imperial) | 0.1   |
| Bundle Diameter Min (Metric)   | 2.54  |
| Bundle Diameter Max (Imperial) | 0.37  |
| Bundle Diameter Max (Metric)   | 9.5   |
| Diameter D (Imperial)          | 0.38  |
| Diameter D (Metric)            | 9.5   |
| Nominal Diameter (Imperial)    | 0.38  |
| Nominal Diameter (Metric)      | 9.5   |

|                               |   |
|-------------------------------|---|
| Wall Thickness WT (Imperial)  | 0.027   |
| Wall Thickness WT (Metric)    | 0.68  |
| Material                      | Polyester (PET)                                       |
| Material Shortcut             | PET   |
| Flammability                  | UL VW-1   |
| Halogen Free                  | Yes   |
| UV Resistant (Yes/No)         | No  |
| Use Conditions                | For Indoor Use Only                                   |
| Operating Temperature         | -94°F to +257°F (-70°C to +125°C)                     |
| Reach Compliant (Article 33)  | Yes   |
| ROHS Compliant                | Yes   |
| Certification/Specification   | ASTM E 662 Exova   NFPA130: 2017 ASTM 1354 ASTM E 162 |
| UL Recognized (US)            | Yes   |
| UL Recognized (US and Canada) | Yes   |
| Package Quantity (Imperial)   | 250   |

Package Quantity (Metric) 76.20

Customs Number 5806322000

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)