

## Specification Sheet

Part Number: 211-60079



P-Clamps easily guide and locate wire and cables up to 1" in diameter.

Designed with a radius edge to prevent chafing and cutting into insulation.

P-Clamp, 0.39" Wide, 0.49" Max Bundle Dia, 0.17" Mounting Hole Dia, PA66, Natural, 1000/pkg

Article Number 211-60079

Type H7P

Color Natural (NA)

Quantity Per pack

Product Description HellermannTyton P-Clamps easily guide and locate wires and cables. The clamps are designed with a radius edges to prevent chafing and cutting into insulation. Available sizes up to 1" bundle diameters.

Short Description P-Clamp, 0.39" Wide, 0.49" Max Bundle Dia, 0.17" Mounting Hole Dia, PA66, Natural, 1000/pkg

Global Part Name H7P-PA66-NA

|                                       |                      |
|---------------------------------------|----------------------|
| Fixation Method                       | screw-hole           |
| Variant                               | Closed               |
| Width W (Imperial)                    | 0.39                 |
| Width W (Metric)                      | 10.0                 |
| Bundle Diameter Max (Imperial)        | 0.49                 |
| Bundle Diameter Max (Metric)          | 12.5                 |
| Nominal Diameter (Imperial)           | 0.5                  |
| Nominal Diameter (Metric)             | 12.5                 |
| Wall Thickness WT (Imperial)          | 0.047                |
| Wall Thickness WT (Metric)            | 1.2                  |
| Mounting Hole Diameter D (Imperial)   | 0.17                 |
| Mounting Hole Diameter D (Metric)     | 4.2 mm               |
| Mounting Hole Diameter D Max (Metric) | 4.2                  |
| Mounting Hole Centers (Imperial)      | 0.55                 |
| Material                              | Polyamide 6.6 (PA66) |

|                              |                                  |
|------------------------------|----------------------------------|
| Material Shortcut            | PA66                             |
| Flammability                 | UL 94 V-2                        |
| UV Resistant (Yes/No)        | No                               |
| Use Conditions               | For Indoor Use Only              |
| Operating Temperature        | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33) | Yes                              |
| ROHS Compliant               | Yes                              |
| Certification/Specification  | EN [45545-2]                     |
| Package Quantity (Imperial)  | 1000                             |
| Package Quantity (Metric)    | 1000                             |
| Customs Number               | 3926909988                       |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)