

Specification Sheet

Part Number: TAG52L-105

Laser printable self-laminating polyester has a smooth surface, allowing for the highest resolution and print contrast.

The material is 1.0 mil thick, allowing it to conform around wires and cable.

The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Lasertags are not affected by the high heat required in a laser printer.



Laser Tag Label, Self-Laminating, 2.0" x .47" x 1.33", 21 Per Sheet, PET, White, 1000/pkg

Article Number 594-52105

Type TAG52L

Color White (WH)

Quantity Per pack

Product Description HellermannTyton's self-laminating labels are used for marking wires and cable. The clear tail overlaps and protects the printed information from abrasion, chemicals and solvents and resists UV exposure. When printed using a laser printer, clear marking and high high-contrast imaging against the wire make this the perfect choice for durable identification.

| | |
|---------------------------------|-------------------------------------------------------------------------------------------|
| Short Description | Laser Tag Label, Self-Laminating, 2.0" x .47" x 1.33", 21 Per Sheet, PET, White, 1000/pkg |
| Global Part Name | TAG52L-105-WH |
| Width W (Imperial) | 2.0 |
| Width W (Metric) | 50.8 |
| Bundle Diameter Min (Imperial) | 0.25 |
| Bundle Diameter Min (Metric) | 6.35 |
| Bundle Diameter Max (Imperial) | 0.46 |
| Bundle Diameter Max (Metric) | 11.60 |
| Thickness T (Metric) | 35.0 |
| Width of Liner (Metric) | 215.00 |
| Width of Liner (Imperial) | 8.5 |
| Outside Diameter Max (Imperial) | 0.299 |
| Outside Diameter Min (Metric) | 3.8 |
| Outside Diameter Min (Imperial) | 0.15 |
| Outside Diameter Max (Metric) | 7.60 |

| | |
|--------------------------------|-----------------------------------|
| Material | Type 105, Polyester, white (105) |
| Material Shortcut | 105 |
| Adhesive | Acrylic |
| Halogen Free | No |
| UV Resistant (Yes/No) | No |
| Use Conditions | For Indoor Use Only |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Operating Temperature | -40°F to +300°F (-40°C to +149°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 1000 |
| Package Quantity (Metric) | 1000 |
| Customs Number | 3919905060 |
| Labels per Column | 7 |
| Labels per Row | 3 |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)