


Specification Sheet

Part Number: 904-00244



Strong fingers prevent unintended breaking.

Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct.

Restricted opening design in the finger of the duct helps keep wires in place, preventing unintended removal and permitting individual wires to be traced without disconnection.

Slotted Wall Wiring Duct, 2" x 1", Non-Adhesive, 7 ft Long, PVC, Gray, 140 ft/Carton

Article Number	904-00244
Type	SL2X1
Color	Gray (GY)
Quantity Per	pack
Product Description	Slotted Wall Wiring Duct features break-away fingers that provide easy access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a greater opening is required. The lower score line allows the sidewall to be smoothly cut for joints and T's.
Short Description	Slotted Wall Wiring Duct, 2" x 1", Non-Adhesive, 7 ft Long, PVC, Gray, 140 ft/Carton

Global Part Name	SL2X1-PVC-GY
Length L (Imperial)	7.0
Length L (Metric)	2.13
Fixation Method	Non-Adhesive
Width W (Imperial)	2.0
Width W (Metric)	50.8
Height H (Imperial)	1.06
Height H (Metric)	26.9
Mounting Hole Centers (Imperial)	4.0
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	UL 94 V-0
Halogen Free	No
Use Conditions	For Indoor Use Only
Operating Temperature	+122°F (+50°C)

Reach Compliant (Article 33)	No
ROHS Compliant	Yes
UL Recognized (US)	Yes
Package Quantity (Imperial)	140.0
Package Quantity (Metric)	42.67
Customs Number	3925900000

7930 N. Faulkner Road, Milwaukee, WI 53224
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.
[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)