

Specification Sheet

Part Number: ATS10266210



Available in packages of 5,000 closures for high-volume applications.

Cable Tie Closures for ATS Systems, 50lb Tensile Strength, PA66HSUV, Black, 5000/reel

Article Number	102-66210
Type	Closures_Black_ATS
Color	Black (BK)
Quantity Per	pcs.
Product Description	The cable tie closure for the ATS Flex is designed for optimized material utilization. This innovative two-piece system consists of a separate strap and closure, eliminating waste and the associated jobsite cleanup.
Short Description	Cable Tie Closures for ATS Systems, 50lb Tensile Strength, PA66HSUV, Black, 5000/reel
Global Part Name	Closures_Black_ATS-PA66HSUV-BK

Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	0.35
Length L (Metric)	9.0
Identification Plate Position	none
Reel Diameter (Imperial)	15.25
Reel Diameter (Metric)	387
Reel Width (Imperial)	3.5
Reel Width (Metric)	88.9
Releasable Closure	No
Variant	closures on reel
Width W (Imperial)	0.31
Width W (Metric)	8.0
Bundle Diameter Min (Metric)	0.0
Bundle Diameter Max (Imperial)	3.94
Bundle Diameter Max (Metric)	100

Height H (Imperial)	0.212
Height H (Metric)	5.4
Material	Polyamide 6.6 heat and UV stabilized (PA66HSUV)
Material Shortcut	PA66HSUV
Flammability	UL 94 V-2
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	5000
Package Quantity (Metric)	5000
Customs Number	3926909988
Reel Weight (Imperial)	3.5
Reel Weight (Metric)	1.58

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)