

## Specification Sheet

Part Number: T30RA300HS



The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs.

Available in reels of 3,000 each or bandoliers of 30 each.

Cable Ties for AT2060, 30lb Tensile Strength, PA66HS, Black, 30/bandolier, 600/pkg

|                     |                                                                                                  |
|---------------------|--------------------------------------------------------------------------------------------------|
| Article Number      | 103-00003                                                                                        |
| Type                | T30RA                                                                                            |
| Color               | Black (BK)                                                                                       |
| Quantity Per        | bag                                                                                              |
| Product Description | Includes AT2060 tool, power supply, power cord, tool cord, and maintenance and operation manual. |
| Short Description   | Cable Ties for AT2060, 30lb Tensile Strength, PA66HS, Black, 30/bandolier, 600/pkg               |
| Global Part Name    | T30RA-PA66HS-BK                                                                                  |

|                                     |           |
|-------------------------------------|-----------|
| Minimum Tensile Strength (Imperial) | 30        |
| Minimum Tensile Strength (Metric)   | 133.4     |
| Length L (Imperial)                 | 6.0       |
| Length L (Metric)                   | 152.4     |
| Identification Plate Position       | none      |
| Reel Diameter (Imperial)            | 17.7      |
| Reel Diameter (Metric)              | 450.0     |
| Reel Width (Imperial)               | 7.197     |
| Reel Width (Metric)                 | 182.8     |
| Voltage Range                       | 27 Volt   |
| Releasable Closure                  | No        |
| Variant                             | bandolier |
| Width W (Imperial)                  | 0.14      |
| Width W (Metric)                    | 3.6       |
| Bundle Diameter Min (Imperial)      | 0.06      |
| Bundle Diameter Min (Metric)        | 1.5       |
| Bundle Diameter Max (Imperial)      | 1.25      |

|                               |                                        |
|-------------------------------|----------------------------------------|
| Bundle Diameter Max (Metric)  | 31.75                                  |
| Thickness T (Imperial)        | 0.05                                   |
| Thickness T (Metric)          | 1.2                                    |
| Cycle Time                    | 1.2 seconds                            |
| Tension Setting Tools         | Adjustable                             |
| Power Supply                  | Electrical                             |
| Material                      | Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut             | PA66HS                                 |
| Flammability                  | UL 94 V-2                              |
| UV Resistant (Yes/No)         | No                                     |
| Use Conditions                | For Indoor and Outdoor Use             |
| Operating Temperature         | -40°F to +275°F (-40°C to +135°C)      |
| Reach Compliant (Article 33)  | No                                     |
| UL Recognized (US)            | Yes                                    |
| UL Recognized (US and Canada) | Yes                                    |

|                             |            |
|-----------------------------|------------|
| Package Quantity (Imperial) | 600        |
| Package Quantity (Metric)   | 600        |
| Customs Number              | 3926909988 |
| Reel Weight (Imperial)      | 7          |
| Reel Weight (Metric)        | 3.175      |