

## **Specification Sheet**

Part Number: 106-60000

Apply 8,000 cable ties with a fully charged Metabo 2.0 Ah battery, for virtually non-stop performance.

Removable handle for space-saving integration into fully automated production lines (Power Pack CPK with control box required).

HT Data Management CPK software included for extensive data evaluation and export function for manufacturing data, further service functions and consistent documentation of every binding process.

Bandoliers of 50 cable ties as well as reels of 5,000 cable ties can be used.

Process-reliable, constant and reproducible bundling and cutting up to 20 mm in diameter.



CPK Hybrid T18RA Automatic Cable Tie Tool, 1/pkg

Article Number 106-60000

Type Autotool\_CPK\_hybrid

Color Dark Blue (DKBU)

Quantity Per case

Product Description	The CPK Hybrid (T18RA) is a fully automated cable tying system. It can be powered two ways - electrically with a power pack or with a common CAS lithium-ion battery. It can speed up bundling processes and improve consistency and efficiency. With a single pull of the trigger, the CPK Hybrid delivers a cable tie, wraps it around the bundle, tensions and cuts off the tail. This cable tying system is characterized by its simple operation and user-friendly ergonomics. The CPK Hybrid has preset options and offers an on-tool display for optional setting changes. Increase ergonomics with additional accessories such as the bench mount or overhead suspension options.			
Short Description	CPK Hybrid T18RA Automatic Cable Tie Tool, 1/pkg			
Global Part Name	Autotool_CPK_hybrid-MET/PL-BU			
Minimum Tensile Strength (Imperial)	17.98			
Minimum Tensile Strength (Metric)	82			
Length L (Imperial)	11.22			
Length L (Metric)	285.0			
Width W (Imperial)	3.39			
Width W (Metric)	86.0			
Bundle Diameter Min (Imperial)	0.03			

0.7

0.79

20

Bundle Diameter Min (Metric)

Bundle Diameter Max (Imperial)

Bundle Diameter Max (Metric)

Cable Ties T18RA50, T18RA5000 Cycle Time 0.65-1.0 sec. depending on quality and force Power supply unit Electrical 10.63 Height H (Imperial) Height H (Metric) 270.0 **Tension Setting Tools** Adjustable **Power Supply** 120VAC or 18V battery Material Metal (MET) Plastic (PL) **Material Shortcut** MET PL UV Resistant (Yes/No) No **Use Conditions** For Indoor Use Only Reach Compliant (Article 33) No **ROHS Compliant** Yes Package Quantity (Imperial) 1

1

Package Quantity (Metric)

Customs Number	84672	90095		
© 2024 HellermannTyton. All Rights Reso		DoUS/METE Compliance	Diaglaimar	Tarma and Canditions
	Contact Us	RoHS/WEEE Compliance	Disclaimer	Terms and Conditions