

Specification Sheet

Part Number: 110-88032

Cuts ties from 50 to 255 lb with a clean, flush cut for personnel safety and wire insulation integrity.

Quality construction with impact-resistant housing, tested at over 1 million cycles, provides high durability resulting in fewer repairs and an extended product life.

Lightweight tool with the most technologically advanced ergonomic design for reducing work-related risks such as fatigue and injury that affect productivity.

Tension dial offers 33 precise, easy-to-read settings that reduce subjectivity or the need for fine tuning.



Tension lock-in mechanism prevents operator from changing tension setting during critical applications.

EVO 9iSP Mechanical Hand Tool, Tension Range 12 - 69 lb Short Hand Span, 1/pkg

Article Number	110-88032
Type	EVO9iSP
Color	Blue (BU) Gray (GY)
Quantity Per	box

Product Description	HellermannTyton's EVO 9i industrial-grade, mechanical hand tool is ergonomically designed to reduce the risks of repetitive stress injuries to operators while simultaneously increasing productivity. The EVO 9i Tension/Lock/Cut Technology delivers performance, safety and comfort for operators. Calibrated tensioning ensures consistent wire-bundle tension before flush cut-off. Available in a standard grip span (EVO 9i) or short grip span (EVO 9iSP) for smaller hands. Additional accessories are available.
Short Description	EVO 9iSP Mechanical Hand Tool, Tension Range 12 - 69 lb Short Hand Span, 1/pkg
Global Part Name	EVO9iSP-MET/PL-BU/GY
Tension Setting Tools	Adjustable
Material	Plastic (PL) Metal (MET)
Material Shortcut	PL MET
Use Conditions	For Indoor and Outdoor Use
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1
Package Quantity (Metric)	1

Customs Number

8205599000

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)