

## Specification Sheet


Part Number: T50I2M4UL

Engineered and manufactured for maximum performance and quality

Made from 100% high-quality plastic to ensure efficient recycling

Inside serration for a strong grip onto bundles

Easy application either manually or with a processing tool



Cable Tie, 12" Long, UL Rated, 50lb Tensile Strength, PA66, Red, 1000/pkg

Article Number 111-00519

Type T50I

Color Red (RD)

Quantity Per bag

Product Description T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Cable Tie, 12" Long, UL Rated, 50lb Tensile Strength, PA66, Red, 1000/pkg

Global Part Name T50I-PA66-RD

Minimum Tensile Strength (Imperial) 50

Minimum Tensile Strength (Metric) 225

Length L (Imperial) 12.0

Length L (Metric) 305.0

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.18

Width W (Metric) 4.6

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Min (Metric) 1.5

Bundle Diameter Max (Imperial) 3.15

Bundle Diameter Max (Metric) 80.0

Cable Tie Head Length (Imperial) 0.27

|                                 |                                  |
|---------------------------------|----------------------------------|
| Cable Tie Head Width (Imperial) | 0.31                             |
| Material                        | Polyamide 6.6 (PA66)             |
| Material Shortcut               | PA66                             |
| Flammability                    | UL 94 V-2                        |
| Halogen Free                    | Yes                              |
| UV Resistant (Yes/No)           | No                               |
| Use Conditions                  | For Indoor Use Only              |
| Plenum Rating                   | AH-2                             |
| Operating Temperature           | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33)    | No                               |
| ROHS Compliant                  | Yes                              |
| Certification/Specification     | UL 62275                         |
| UL Recognized (US)              | Yes                              |
| UL Listed (US and Canada)       | Yes                              |
| UL Recognized (US and Canada)   | Yes                              |

|                             |            |
|-----------------------------|------------|
| UL Listed (US)              | Yes        |
| Package Quantity (Imperial) | 1000       |
| Package Quantity (Metric)   | 1000       |
| Customs Number              | 3926909988 |

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)