

## Specification Sheet

Part Number: 111-12851



Made from 100% high-quality plastic to ensure efficient recycling.

Inside serrations produce strong grip on cables and wire bundles.

Easy application either manually or with a tensioning tool.

Bent tail ensures a quick and simple installation.

Cable Tie, 24.9" Long, 120lb Tensile Strength, PA66, Natural, 50/pkg

Article Number 111-12851

Type T120XLM

Color Natural (NA)

Quantity Per bag

**Product Description** Heavy-Duty T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. The bent tail allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Cable Tie, 24.9" Long, 120lb Tensile Strength, PA66, Natural, 50/pkg

Global Part Name T120XLM-PA66-NA

Minimum Tensile Strength (Imperial) 120

Minimum Tensile Strength (Metric) 535

Length L (Imperial) 24.9

Length L (Metric) 632

Identification Plate Position none

Releasable Closure No

Variant Inside Serrated

Width W (Imperial) 0.30

Width W (Metric) 7.6

Bundle Diameter Min (Imperial) 0.2

Bundle Diameter Min (Metric) 5.0

Bundle Diameter Max (Imperial) 7.24

Bundle Diameter Max (Metric) 184.0

Thickness T (Imperial) 0.07

Thickness T (Metric) 1.9

Cable Tie Head Length (Imperial)	0.39
Cable Tie Head Width (Imperial)	0.51
Height H (Imperial)	0.31
Height H (Metric)	7.8
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Use Conditions	For Indoor Use Only
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3926909988

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)