


Specification Sheet

Part Number: 111-91001



The 316 grade stainless steel offers excellent resistance to salt spray, corrosion, weather and chemicals.

Polyester coating prevents contact corrosion with dissimilar metals.

Releasable – once installed, they can be opened and re-used if required.

Stainless Steel Cable Tie, 9" Long, SS316, 100/pkg

Article Number 111-91001

Type MLT8SSC10

Color Black (BK)

Quantity Per bag

Product Description The MLT range of stainless steel cable ties can be used in harsh conditions or where the additional security, strength and fire resistance of a metal fastener is required. Ideal for use in mass transit, shipbuilding, oil rigs, mining and chemicals, theaters and exhibition halls.

Short Description Stainless Steel Cable Tie, 9" Long, SS316, 100/pkg

Global Part Name MLT8SSC10-SS316L/SP-BK

Minimum Tensile Strength (Imperial)	191
Minimum Tensile Strength (Metric)	850
Length L (Imperial)	9.0
Length L (Metric)	230
Identification Plate Position	none
Releasable Closure	Yes
Tie Closure	folding
Variant	Not Serrated
Width W (Imperial)	0.40
Width W (Metric)	10.26
Bundle Diameter Min (Imperial)	0.98
Bundle Diameter Min (Metric)	25.0
Bundle Diameter Max (Imperial)	2.36
Bundle Diameter Max (Metric)	60
Thickness T (Imperial)	0.03
Thickness T (Metric)	0.7

Material	Polyester (SP) Stainless Steel (SS316L)
Material Shortcut	SP SS316L
Flammability	Non-burning (except coating)
Halogen Free	Yes
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-112°F to +1000°F (-80°C to +538°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	7326908695