

Specification Sheet

Part Number: T18MR0C2



Screw mount style creates low insertion and high extraction force.

Choose from several tensile strengths and lengths to accommodate a range of applications.

1-Piece Cable Tie/Screw Mount, 4.3" Long, #4 Screw, 0.79" Max Bundle Dia, 18lb, PA66HS, Black, 100/pkg

Article Number 113-00022

Type T18MR

Color Black (BK)

Quantity Per bag

Product Description 1-piece Screw Mount Cable Ties fasten with a screw or bolt to provide secure routing of cable bundles. Multiple configurations are available to cover a range of bundle sizes and tensile strengths.

Short Description 1-Piece Cable Tie/Screw Mount, 4.3" Long, #4 Screw, 0.79" Max Bundle Dia, 18lb, PA66HS, Black, 100/pkg

Global Part Name T18MR-PA66HS-BK

| | |
|-------------------------------------|-----------------|
| Minimum Tensile Strength (Imperial) | 18 |
| Minimum Tensile Strength (Metric) | 80 |
| Length L (Imperial) | 4.3 |
| Length L (Metric) | 110.0 |
| Fixation Method | Screw Mount |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.1 |
| Width W (Metric) | 2.5 |
| Bundle Diameter Min (Imperial) | 0.06 |
| Bundle Diameter Min (Metric) | 1.5 |
| Bundle Diameter Max (Imperial) | 0.79 |
| Bundle Diameter Max (Metric) | 20.0 |
| Thickness T (Imperial) | 0.039 |

| | |
|---------------------------------------|--|
| Thickness T (Metric) | 1.0 |
| Height H (Imperial) | .17 |
| Height H (Metric) | 4.20 |
| Mounting Hole Diameter D (Imperial) | 0.12 |
| Mounting Hole Diameter D (Metric) | 3.1 mm |
| Mounting Hole Diameter D Max (Metric) | 3.1 |
| Material | Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut | PA66HS |
| Flammability | UL 94 V-2 |
| UV Resistant (Yes/No) | No |
| Use Conditions | For Indoor and Outdoor Use |
| Plenum Rating | AH-2 |
| Operating Temperature | -40°F to +257°F (-40°C to +125°C) |
| Reach Compliant (Article 33) | No |
| ROHS Compliant | Yes |

| | |
|-------------------------------|------------|
| Certification/Specification | UL 62275 |
| UL Recognized (US) | Yes |
| UL Listed (US and Canada) | Yes |
| UL Recognized (US and Canada) | Yes |
| UL Listed (US) | Yes |
| Package Quantity (Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909988 |

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)