

Specification Sheet

Part Number: 115-00047

Release feature allows maintenance or changeouts as needed.

Polyamide 6.6 cable ties deliver excellent resistance to chemicals and salts.

Inside serrations provide strong grip on cables and wire bundles.

Reliable bundle fastening plus low insertion force for ease of use.



Releasable Cable Tie, Release Lever, 5.5" Long, 50lb Tensile Strength, PA66, Natural, 100/pkg

Article Number 115-00047

Type RF140

Color Natural (NA)

Quantity Per bag

Product Description Releasable Cable Ties feature an integrated release mechanism on the head, allowing for changeouts without destroying the cable tie. The head design ensures consistently high tensile strength, even after repeated use. Rounded tail glides into head with low insertion force.

Short Description Releasable Cable Tie, Release Lever, 5.5" Long, 50lb Tensile Strength, PA66, Natural, 100/pkg

Global Part Name RF140-PA66-NA

| | |
|-------------------------------------|----------------------|
| Minimum Tensile Strength (Imperial) | 50 |
| Minimum Tensile Strength (Metric) | 225 |
| Length L (Imperial) | 5.5 |
| Length L (Metric) | 140.0 |
| Fixation Method | Releasable Cable Tie |
| Identification Plate Position | none |
| Releasable Closure | Yes |
| Width W (Imperial) | 0.29 |
| Width W (Metric) | 7.4 |
| Bundle Diameter Min (Imperial) | 0.1 |
| Bundle Diameter Min (Metric) | 2.5 |
| Bundle Diameter Max (Imperial) | 1.26 |
| Bundle Diameter Max (Metric) | 32.0 |
| Thickness T (Metric) | 1.2 |
| Material | Polyamide 6.6 (PA66) |

| | |
|------------------------------|----------------------------------|
| Material Shortcut | PA66 |
| Flammability | UL 94 V-2 |
| UV Resistant (Yes/No) | No |
| Use Conditions | For Indoor Use Only |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33) | No |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909988 |